

2019 Carbide Cutter Generation 4 Forestry Mulching Heads for Skid-steers



Features

- **Choose from 3 Tooth Designs** - Ultra-sharp Quadco Reversible Knives, Quadco Hard-surfaced or Rugged Double Carbide Teeth
- **Two-stage Cutting Chamber** - 2 Shear Bars Producing a Finer Mulch with Less Passes
- Variable Disp. Piston-type Motor 80-110 cc
- Fixed Disp. High Pressure Gear-type Motor
- Heavy-duty Bearing Block
- Re-cutter Bar at Discharge
- Adjustable Bolt-in 2nd Shear Bar
- Machined Bearing Anti-wrap
- Efficient Staggered Carbide Tooth Pattern
- Premium Strength Steel Housing
- Increased Visibility
- 1600-2300 Rotor rpm
- 17 inch Diameter Rotor
- 2-3/16" Piloted Double Taper Roller Bearings
- Synchronous Belt
- On-board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Adjustable Skid Shoes -1.5 to +0.5 inches
- Hoses are included. (no couplers)
- Adjustable Tree-pusher Bar
- Universal Skid-steer Mount
- Welded Claw Hooks on Pusher Bar
- Improved Hose Routing

2019 Retail Pricing - CARBIDE G4 MULCHING HEAD

Specs	Width of Cut in Inches	61	71
	Overall Width in Inches	76.2	86.2
	Number of Teeth	36	42
	Weight in Pounds	2505	2706
	Crated Weight in Pounds	2725	2925

Circle/select 1 item from each of 5 groups in the proper size/model column and code column.

Group	Carbide Cutter G4	CODE	61	71
1	Size			
	61 inches	61G4	\$18,715	
	71 inches	71G4		\$19,825
2	Teeth			
	Standard Double Carbide - N15510 (\$80.00 ea.)	S	\$2,940	\$3,430
	Quadco Reversible Knives - N24279 (\$37.00 ea.)	Q	\$3,120	\$3,650
	Hard-surfaced Quadco Reversible Knives - 200011 (\$57.00 ea.)	H	\$3,840	\$4,490
3	Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)			
	Variable Displacement Piston Motor - 50-120 Hydraulic Horsepower	39	\$8,650	\$8,650
	Fixed Disp. High Pressure Gear Motor - 50-85 Hydraulic Horsepower	38	\$3,650	\$3,650
4	Auxiliary Hydraulic Flow (GPM)			
	33-37 GPM (Variable Disp. Motor) up to 6000 PSI	A	\$0	\$0
	38-42 GPM (Variable Disp. Motor) up to 6000 PSI	B	\$0	\$0
	43-45 GPM (Variable Disp. Motor) up to 6000 PSI	D	\$0	\$0
	28-30 GPM (Fixed Disp. Motor) up to 4300 PSI	E	\$0	\$0
	31-35 GPM (Fixed Disp. Motor) up to 4300 PSI	F	\$0	\$0
	36-40 GPM (Fixed Disp. Motor) up to 4300 PSI	G	\$0	\$0
5	Auxiliary Hydraulic Pressure (psi)			
	Fixed Displacement High Pressure Gear Motor	0	\$0	\$0
	2800-3400 PSI (Variable Displacement Motor System)	1	\$0	\$0
	3400-3800 PSI (Variable Displacement Motor System)	2	\$0	\$0
	3800-4200 PSI (Variable Displacement Motor System)	3	\$0	\$0

Product Code: _____ Total List Price \$ _____
 Groups 1 2 3 4 5

Hoses are included. - Couplers are NOT included.

Variable Motor: 1" with -16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring
 Fixed Motor: 3/4" with -12 MORB Male O-ring, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring
 Crating Charge (net price) \$ 165 \$ 175

Other Related Products Auxiliary Hydraulic Oil Cooler, Skid-steer Mounted, Heavy-duty 120,000 BTU Cooler with Dual Fans For Heavy-duty Applications - Ask for the "Cool Flow" cooler from Loftness



650 South Main Street
 Hector, Minnesota 55342
 loftness.com - 320.848.6266