

2019 “Battle Ax” Forestry Mulching Heads for Skid-steers



Features

- **All NEW “Battle Ax” Rotor Design** - Uses Built-in “Depth Gauges” to Control Cutting Depth, like “Raker” Teeth on a Chainsaw
- **Two-stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch with Less Passes
- **Choose from 3 Tooth Designs** - Ultra-sharp Quadco Reversible Knives, Quadco Hard-surfaced or Rugged Double Carbide Teeth
- Efficient Staggered/Spiral Tooth Pattern
- Increased Visibility
- Variable Disp. Piston-type Motor 80-110 cc
- Fixed Disp. High Pressure Gear-type Motor
- Adjustable Primary Shear Bar
- Premium Strength Steel Housing
- 1600-2500 Rotor rpm
- 17 inch Diameter Rotor
- 2-3/16” Piloted Double Taper Roller Bearings
- Machined Bearing Anti-wrap
- Synchronous Belt Drive
- On-board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Adjustable Skid Shoes -1.5 to +0.5 inches
- Adjustable Tree-pusher Bar
- Welded Claw Hooks on Pusher Bar
- Hoses are included. (no couplers)
- Improved Hose Routing
- Universal Skid-steer Mount

800.828.7624 - loftness.com - 320.848.6266

2019 Retail Pricing - *Battle Ax Skid-steer*

Specs	Width of Cut in Inches	61	71
	Overall Width in Inches	76.2	86.2
	Number of Teeth	30	36
	Weight in Pounds	2500	2700
	Crated Weight in Pounds	2725	2925

Circle/select 1 item from each of 5 groups in the proper size/model column and code column.

Group	Battle Ax Skid-steer	CODE	61	71
1	Size			
	61 inches	61BS	\$19,958	
	71 inches	71BS		\$21,078
2	Teeth			
	Quadco Reversible Knives - N49366 (\$40.00 ea.)	Q	\$1,200	\$1,440
	Hard-surfaced Quadco Reversible Knives - 203014 (\$60.00 ea.)	H	\$1,800	\$2,160
	Standard Double Carbide - N49090 (\$80.00 ea.)	S	\$2,400	\$2,880
3	Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)			
	Variable Displacement Piston Motor - 50-120 Hydraulic Horsepower	39	\$8,650	\$8,650
	Fixed Disp. High Pressure Gear Motor - 50-85 Hydraulic Horsepower	38	\$3,650	\$3,650
4	Auxiliary Hydraulic Flow (GPM)			
	33-37 GPM (Variable Disp. Motor) up to 6000 PSI Standard Speed	A	\$0	\$0
	38-42 GPM (Variable Disp. Motor) up to 6000 PSI Standard Speed	B	\$0	\$0
	43-45 GPM (Variable Disp. Motor) up to 6000 PSI Standard Speed	D	\$0	\$0
	32-36 GPM (Variable Disp. Motor) up to 6000 PSI High Speed Option	T	\$0	\$0
	37-41 GPM (Variable Disp. Motor) up to 6000 PSI High Speed Option	U	\$0	\$0
	42-45 GPM (Variable Disp. Motor) up to 6000 PSI High Speed Option	V	\$0	\$0
	28-30 GPM (Fixed Disp. Motor) up to 4300 PSI	E	\$0	\$0
	31-35 GPM (Fixed Disp. Motor) up to 4300 PSI	F	\$0	\$0
	36-40 GPM (Fixed Disp. Motor) up to 4300 PSI	G	\$0	\$0
5	Auxiliary Hydraulic Pressure (psi)			
	Fixed Displacement High Pressure Gear Motor	0	\$0	\$0
	2800-3400 PSI (Variable Displacement Motor System)	1	\$0	\$0
	3400-3800 PSI (Variable Displacement Motor System)	2	\$0	\$0
	3800-4200 PSI (Variable Displacement Motor System)	3	\$0	\$0

Product Code: _____ Total List Price \$ _____
 Groups 1 2 3 4 5

Hoses are included. - Couplers are NOT included.

Variable Motor: 1" with -16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring
 Fixed Motor: 3/4" with -12 MORB Male O-ring, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring
 Crating Charge (net price) \$ 165 \$ 175

Other Related Products Auxiliary Hydraulic Oil Cooler, Skid-steer Mounted, Heavy-duty 120,000 BTU Cooler with Dual Fans For Heavy-duty Applications - Ask for the "Cool Flow" cooler from Loftness



**650 South Main Street
 Hector, Minnesota 55342
 loftness.com - 320.848.6266**