12 ton Fertilizer Spreaders

Circle/select 1 item from each group in the proper size/model column and code column.

		Weight - Base weight may vary depending on options.	Code	6980 lbs.
Groups		Row Crop Spreader	F1210	\$34,319
Tt.		40' Driving Interval	4	\$0
Spread Width		50' Driving Interval	5	\$0
		60' Driving Interval	6	Included
	1	80' Driving Interval	8	\$0
		88' Driving Interval	A	\$0 \$0
		90' Driving Interval	9	\$0 \$0
	\vdash	380/90R46 (14.9R46) Lugged Tire - Single - 10 on 11.25 BC	В	Included
.		380/90R46 (14.9R46) Lugged Tire - Dual Ready - 10 on 13.189 BC	2	\$1,960
		480/80R42 (18.4R42) Lugged Tire - Single - 10 on 11.25 BC Special Order Only Call Factory	C	\$1,900
Tire Size	2	320/90R50 (12.4R50) Lugged Tire - Dual Ready - 10 on 13.189 BC Special Order Only Call Factory	4	\$5,540
<u>ie</u>	_	710/70R38 Lugged Tire - Single - 10 on 13.189 BC Special Order Only Call Factory	F F	\$9,160
Ē		No Tires - 10 on 11.25 BC		(\$2,600)
		No Tires - 10 on 13.189 BC	N H	,
				(\$1,300)
e l		Hydraulic Drive Raven 22 pin - Variable Rate Ready (VRR), requires HSD, not available on CSD	W	\$0
Apron Drive		Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR)	X	Included
lo.	3	Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR) (Two Section)	Y	\$1,660
Apr		Hydraulic Drive ISO ready - Variable Rate Ready (VRR)	Т	\$0
		Hydraulic Drive ISO ready - Variable Rate Ready (VRR) (Two Section)	U	\$1,660
Spinner Drive	4	Hydraulic Spinner Drive (HSD) - Fixed Speed	Н	Included
Spii Dr		Controlled Spinner Drive (CSD) - Compensated Speed - Includes Speed Sensor	С	\$610
		80"-120" Tread on center - Non-steerable	8	Included
Wheel Struts, Steering & Scale Options (no brakes)		80"-120" Tread on center - Non-steerable, w/ Scale (monitor is optional)	9	\$2,790
teer o b		80"-120" Tread on center - Steerable	С	\$2,050
s, Si	5	80"-120" Tread on center - Steerable, w/ Scale (monitor is optional)	D	\$4,760
ruts		90"-152" Tread on center - Non-steerable	А	\$330
l St Opt		90"-152" Tread on center - Non-steerable, w/ Scale (monitor is optional)	В	\$3,030
hee ale		90"-152" Tread on center - Steerable	E	\$2,370
Sca		90"-152" Tread on center - Steerable, w/ Scale (monitor is optional)	F	\$5,080
		Duals- 380/90R46 (14.9R46) Lugged Tire - 20" Spacing (requires #2 group 2)	3	\$8,000
		Duals- 380/90R46 (14.9R46) Lugged Tire - 22"/30" Spacing (requires #2 group 2)	2	\$8,000
2	<u>:</u>	Duals- 320/90R50 (12.4R50) Lugged Tire - 20" Spacing (requires #4 group 2)	5	\$8,000
acto	abil	Duals- 320/90R50 (12.4R50) Lugged Tire - 22"/30" Spacing (requires #4 group 2)	4	\$8,000
Options Please call factory	vail	Tarp, installed	Т	\$2,900
Dpti	a ≥	Raven ISO CAN Node (requires ISO ready)	I	\$4,100
) Sase	erii	Raven SCS660 Controller (req.22 pin) (includes harness to spreader)	R	\$3,980
P.	to	GPS Speed Sensor	G	\$720
		Spinner RPM Sensor (Requires HSD) (included in CSD)	S	\$310
		Scale Monitor - Digistar GT 400 (requires scale)	М	\$1,290

Product Code								Total \$
i ioddci code							·	10ιαι ψ
	model	groups: 1	2	3	4	5	option option option option	

12 ton Lime/Fertilizer/Material Spreaders

Circle/select 1 item from each group in the proper size/model column and code column.

Groups		Weight - Base weight may vary depending on options.	Code	7200 lbs.
Ciou	po 	Lime/Fertilizer/Material	L1230	\$38,039
		40' Driving Interval	4	\$0
dth		50' Driving Interval	5	\$0
Spread Width	1	60' Driving Interval	6	Included
	'	80' Driving Interval	8	\$0
		88' Driving Interval	Α	\$0
		90' Driving Interval	9	\$0
		380/90R46 (14.9R46) Lugged Tire - Single - 10 on 11.25 BC	В	Included
		380/90R46 (14.9R46) Lugged Tire - Dual Ready - 10 on 13.189 BC	2	\$1,960
ze		480/80R42 (18.4R42) Lugged Tire - Single - 10 on 11.25 BC Special Order Only Call Factory	С	\$0
e Si	2	320/90R50 (12.4R50) Lugged Tire - Dual Ready - 10 on 13.189 BC Special Order Only Call Factory	4	\$5,540
Tire Size		710/70R38 Lugged Tire - Single - 10 on 13.189 BC Special Order Only Call Factory	F	\$9,160
		No Tires - 10 on 11.25 BC	N	(\$2,600)
		No Tires - 10 on 13.189 BC	Н	(\$1,300)
		Hydraulic Drive Raven 22 pin - Variable Rate Ready (VRR), requires HSD, not available on CSD	W	\$0
Apron Drive	3	Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR)	Х	Included
₹□		Hydraulic Drive ISO ready - Variable Rate Ready (VRR)	Т	\$0
ner	1	Hydraulic Spinner Drive (HSD) - Fixed Speed	Н	Included
Spinner Drive	4	Controlled Spinner Drive (CSD) - Compensated Speed - Includes Speed Sensor	С	\$610
		80"-120" Tread on center - Non-steerable	8	Included
Wheel Struts, Steering & Scale Options (no brakes)		80"-120" Tread on center - Non-steerable, w/ Scale (monitor is optional)	9	\$2,790
eeri o br		80"-120" Tread on center - Steerable	С	\$2,050
S (ne	_	80"-120" Tread on center - Steerable, w/ Scale (monitor is optional)	D	\$4,760
ruts	5	90"-152" Tread on center - Non-steerable	Α	\$330
l Stı		90"-152" Tread on center - Non-steerable, w/ Scale (monitor is optional)	В	\$3,030
hee ale (90"-152" Tread on center - Steerable	Е	\$2,370
Sca		90"-152" Tread on center - Steerable, w/ Scale (monitor is optional)	F	\$5,080
	_	Duals- 380/90R46 (14.9R46) Lugged Tire - 20" Spacing (requires #2 group 2)	3	\$8,000
		Duals- 380/90R46 (14.9R46) Lugged Tire - 22"/30" Spacing (requires #2 group 2)	2	\$8,000
ج ا	<u>ج</u>	Duals- 320/90R50 (12.4R50) Lugged Tire - 20" Spacing (requires #4 group 2)	5	\$8,000
ctor	iii	Duals- 320/90R50 (12.4R50) Lugged Tire - 22"/30" Spacing (requires #4 group 2)	4	\$8,000
ons II fa	/aila	Tarp, installed	Т	\$2,900
Options e call fa	y a	Raven ISO CAN Node (requires ISO ready)	ı	\$4,100
C	erif	Raven SCS660 Controller (req.22 pin) (includes harness to spreader)	R	\$3,980
Options Please call factory	to <	GPS Speed Sensor	G	\$720
		Spinner RPM Sensor (Requires HSD) (included in CSD)	S	\$310
		Scale Monitor - Digistar GT 400 (requires scale)	М	\$1,290

Product Code:					·	Total \$
model groups: 1	2	3	4	5	option option option option	

8 ton Row Crop Fertilizer Spreaders

Circle/select 1 item from each group in the proper size/model column and code column.

		Weight - Base weight may vary depending on options.	Code	4320 lbs.
Groups		Row Crop Spreader	RC800	\$29,129
		40' Driving Interval	4	\$0
Spread Width		50' Driving Interval	5	\$0 \$0
		<u> </u>	6	
	1	60' Driving Interval		Included
		80' Driving Interval (HSD or CSD Spinner only)	8	\$0
		88' Driving Interval (HSD or CSD Spinner only)	A	\$0
	_	90' Driving Interval (HSD or CSD Spinner only) 380/90R46 (14.9R46) Lugged Tire - Single - 10 on 11.25 BC	9 B	\$0 Included
		380/90R46 (14.9R46) Lugged Tire - Dual Ready - 10 on 13.189 BC	2	\$1,960
		480/80R42 (18.4R42) Lugged Tire - Single - 10 on 11.25 BC Special Order Only Call Factory	C	\$0
ze		320/90R50 (12.4R50) Lugged Tire - Single - 10 on 11.25 BC Special Order Only Call Factory	D	\$3,580
e Tire Size	2	320/90R50 (12.4R50) Lugged Tire - Dual Ready - 10 on 13.189 BC Special Order Only Call Factory	4	\$5,540
		710/70R38 Lugged Tire - Single - 10 on 13.189 BC Special Order Only Call Factory	F	\$9,160
		No Tires - 10 on 11.25 BC	N	(\$2,600)
		No Tires - 10 on 13.189 BC		
on Drive		Mechanical Ground Drive (MGD) w/ hydraulic shut off	H M	(\$1,300) \$1,070
Apron Drive		Hydraulic Drive Raven 16 pin - Variable Rate Ready (VRR), requires HSD	V	\$1,070
	3	Hydraulic Drive Raven 22 pin - Variable Rate Ready (VRR), requires HSD, not available on CSD	W	\$0
		Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR)	X	Included
		Hydraulic Spinner Drive (HSD) - Fixed Speed	Н	Included
Spinner Drive	4	Controlled Spinner Drive (CSD) - Compensated Speed - Includes Speed Sensor	С	\$610
Spi		PTO Driven - 540/1000 input	1	\$1,000
ts (80"-120" Tread on center	8	Included
trui otio		80"-120" Tread on center w/ Scale (requires 10 on 11.25 BC Group 2) (monitor is optional)	9	\$2,450
el S o Or bra	5	90"-152" Tread on center	Α	\$330
Wheel Struts Scale Options (no brakes)		90"-152" Tread on center w/ Scale (requires 10 on 11.25 BC Group 2) (monitor is optional)	В	\$2,790
0,		Duals- 380/90R46 (14.9R46) Lugged Tire - 20" Spacing (requires #2 group 2)	3	\$8,000
		Duals- 380/90R46 (14.9R46) Lugged Tire - 22"/30" Spacing (requires #2 group 2)	2	\$8,000
		Duals- 320/90R50 (12.4R50) Lugged Tire - 20" Spacing (requires #4 group 2)	5	\$8,000
>	÷	Duals- 320/90R50 (12.4R50) Lugged Tire - 22"/30" Spacing (requires #4 group 2)	4	\$8,000
ctor		Tarp, installed	Т	\$2,900
ons I fa	<u>a</u>	Extensions - 11.25", installed	E	\$1,220
Options e call fa	a A	Raven ISO CAN Node (requires ISO ready)	1	\$4,100
Options Please call factory	erii	Raven SCS660 Controller (req.22 pin) (includes harness to spreader)	R	\$3,980
Ble	> 0	GPS Speed Sensor	G	\$720
]	-	Spinner RPM Sensor (Requires HSD) (included in CSD)	S	\$310
		Spinner RPM Display for MGD (includes Spinner RPM sensor)	D	\$1,200
		Scale Monitor - Digistar GT 400 (requires scale)	М	\$1,290

Product Code:							Total \$
	model groups: 1	2	3	4	5	option option option option	

8 ton Flotation Fertilizer Spreaders

	Circle/select 1 item from each group in the proper size/model column and code co	lumn.										
	Weight	Code	4000 lbs									
	Floatation Spreader	FS800	\$25,359									
	Spread Width	•										
	40' Driving Interval	4	\$0									
	50' Driving Interval	5	Included									
1	60' Driving Interval	6	\$0									
	80' Driving Interva (HSD or CSD Spinner only)	8	\$0									
	88' Driving Interval (HSD or CSD Spinner only)	Α	\$0									
	90' Driving Interval (HSD or CSD Spinner only)	9	\$0									
	Tire Size											
2	19L-16.1 Floatation Tire	В	Included									
	VF295/75R22.5 Firestone Destination Radial Farm Implement Tire (Narrow Tire)	D	\$520									
	Apron Drive											
	Mechanical Ground Drive (MGD) w/ hydraulic shut off	М	\$720									
3	Hydraulic Drive Raven 16 pin - Variable Rate Ready (VRR), requires HSD	V	\$0									
	Hydraulic Drive Raven 22 pin - Variable Rate Ready (VRR), requires HSD, not available on CSD	W	\$0									
	Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR), requires HSD or CSD	X	Included									
	Spinner Drive											
	Hydraulic Spinner Drive (HSD) - Fixed Speed	Н	Included									
4	Controlled Spinner Drive (CSD) - Compensated Speed - Includes Speed Sensor	С	\$610									
	PTO Driven - 540 input only	5	\$0									
	PTO Driven - 540/1000 input	1	\$310									
	Tread Width on Center, Brakes											
	74" Tread, No Brakes	8	Included									
5	74" Tread, 2 Wheel Brakes	2	\$900									
	74" Tread, 4 Wheel Brakes	4	\$1,910									
	74" Tread, 4 Wheel Brakes, 9" Rise	5	\$310									
	68" Tread, No Brakes (requires VF295/75R22.5 Tires)	6	\$310									
	Options											
	Tarp, installed	Т	\$2,900									
	Extensions, 11.25", installed	E	\$1,220									
Options	Raven ISO CAN Node (VRR only) (requires 37 pin)	ı	\$4,100									
Opt	Raven SCS660 Controller (VRR only) (req.22 pin) (includes harness to spreader)	R	\$3,980									
	GPS Speed Sensor (VRR only)	G	\$720									
	Spinner RPM Sensor (Requires HSD)(included in CSD)	S	\$310									
	Spinner RPM Display for MGD (includes Spinner RPM sensor)	D	\$1,200									

Product Code:												Total \$
	model	groups: 1	2	3	4	5	option	option	option	option	option	T

1.7 ton Orchard Fertilizer Spreaders

	Circle/select 1 item from each group in the proper size/model column and code co	lumn.											
	Weight	Code	1690 lbs										
	Orchard Spreader	OS170	\$16,619										
	Spread Width												
1	25' Driving Interval	2	Included										
	40' Driving Interval	4	\$0										
2	Tire Size												
2	11L-15 Implement Tire	В	Included										
	Apron Drive												
	Mechanical Ground Drive (MGD) w/ hydraulic shut off	М	Included										
	Mechanical Ground Drive (MGD) w/ rope pull shut off	R	\$0										
3	Mechanical Ground Drive (MGD) w/ hydraulic & rope pull shut off	С	\$490										
	Hydraulic Drive Raven 16 pin - Variable Rate Ready (VRR), requires HSD	V	(\$460)										
	Hydraulic Drive Raven 22 pin - Variable Rate Ready (VRR), requires HSD, not available on CSD	W	(\$460)										
	Hydraulic Drive Raven 37 pin - Variable Rate Ready (VRR), requires HSD or CSD	Х	(\$460)										
	Spinner Drive												
4	Hydraulic Spinner Drive (HSD) - Fixed Speed	Н	Included										
4	Controlled Spinner Drive (CSD) - Compensated Speed - Includes Speed Sensor	С	\$610										
	PTO Driven - 540 input only	5	\$130										
5	Tread Width on Center, (no brakes)												
5	40" Tread center	8	Included										
	Options												
	Screen, not available with Roll-up cover	А	\$1,240										
	Roll-up Cover, installed, not available with Screen	Т	\$1,050										
	Extensions, 11.75", installed	Е	\$1,220										
suc	Raven ISO CAN Node (VRR only) (requires 37 pin)	I	\$4,100										
Options	Raven SCS660 Controller (VRR only) (req.22 pin) (includes harness to spreader)	R	\$3,980										
	GPS Speed Sensor (VRR only)	G	\$720										
	Spinner RPM Sensor (Requires HSD)(included in CSD)	S	\$310										
	Spinner RPM Display for MGD (includes Spinner RPM sensor)	D	\$1,200										
	Banding Attachment	В	\$980										
Pro	duct Code: Total \$	· · · · · ·											
. 10	model groups: 1 2 3 4 5 option option option option												

16 Ton Top Auger Tender



FT1600TA 16 ton, Top Auger

Please Call

16 Ton Rear Auger Tenders



FT160021 16 ton, 21ft x 10in. dia. Rear auger, 10 gal. Reservoir, PTO pump \$ 24,739.00 FT160024 16 ton, 24ft x 10in. dia. Rear auger, 10 gal. Reservoir, PTO pump \$ 26,989.00 FT1600BB 16 ton, NO Auger \$ 19,139.00



8 ton Row Crop Spreader



8 ton Floatation Spreader



1.7 ton Orchard Spreader



650 South Main Street Hector, Minnesota 55342 Ioftness.com - 320.848.6266