

BAD AX - DISC MULCHER

SKID STEER MULCHING HEAD

LOFTNESS



FEATURES

*Forestry Mulching Heads for **Skid Steers***

- Instant Torque Radial Piston High-Pressure Motor
- 36-50 GPM up to 5000 PSI
- 70-120 Hydraulic Horsepower Required
- 60 Inch Diameter Disc - 1.25" Max Thickness
- No Welding on Disc - **Fully Machined**
- 200 MPH Tip Speed @ Up to 1100 RPM
- Quadco Reversible Teeth
- **Bolt-on Replaceable Tooth Mounts**
- Bearing Anti-Wrap Protection
- Premium Strength Steel Body & Disc
- Controlled Discharge Deflector
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Re-Cutter Bar
- Pressure Gauge to Monitor Capacity
- Anti-Cavitation Shut Down Circuit
- Universal Skid-Steer Mount
- Hoses Are Included (Couplers Are Not)

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	60
	Overall Width in Inches	67
	Number of Teeth	44
	Weight Without Mount in Pounds	2643
	Crated Weight in Pounds	2793
	Hydraulic Horsepower Required (Hydraulic HP = GPM X PSI/1714)	70-120
	Radial Piston Motor Max Hydraulic Pressure in PSI	5000

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	60
	Teeth		
1	Quadco 4 Point Beaver Teeth - N156042 (\$20.00 ea.)	60BA	\$22,511
	Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)		
2	36-50 GPM - Piston Motor - 5000 PSI - 70-120 Hydraulic HP	4	\$6,240

PRODUCT CODE			\$
GROUP	1	2	TOTAL LIST PRICE

NOTE: Hoses Are Included. **Couplers Are NOT Included.**

*Main Hoses: 1" with #16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 120,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM



USD - FOB Factory - Uncrated - Prices Effective 4/1/21 (Subject to Change)
650 South Main Street | Hector, MN 55342