

FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC

LOFTNESS 

flail  **HYDRO**
MOWER

FEATURES

Flail Mowers for Skid Steers

- **NEW** - High Pressure Gear-Type Motor
- 26-43 GPM up to 4300 PSI
- Standard Gear Motor (With or Without Case Drain)
- 13-26 GPM up to 3400 PSI
- **Heavy-Duty, Bearing Block**
- 3-Groove Banded Belt
- **0 - 4 1/2 Inch Cutting Height** (Roller Adjustment)
- 1/4 Inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 Inch Bearing on Gauge Roller
- 1900-2200 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-Loaded Belt Tightener
- Full-Width Gauge Roller w/Roller Scraper
- Fine-Cut, Reversible Knives
- 1 3/4 Inch Rotor Bearings
- 10 Gauge Hood
- **Easy Access** Vented Belt Shield
- Hoses Are Included (Couplers Are Not)

(800)828-7624 / (320)848-6266**LOFTNESS.COM****BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	72	90
	Overall Width in Inches	84	102
	Number of Knives HP Required	96	120
	Weight in Pounds	1008	1208
	Crated Weight in Pounds	1275	1475
	Max Hydraulic Pressure (PSI) - Standard Gear Motor	3400	3400
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor	4300	4300
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →			PRODUCT CODE	72	90
Size						
1	72 Inches	72HM	\$8,391			
	90 Inches	90HM			\$9,031	
Hydraulic System						
2	#1 - No Case Drain	1	\$3,090	\$3,090		
	#2 - With Case Drain	2	\$2,400	\$2,400		
Auxiliary Hydraulic Flow (GPM) & Pressure (PSI)						
3	13-15.9 GPM (System #1) 3400 PSI max	02F	\$0	N/A		
	16-18.9 GPM (System #1) 3400 PSI max	03F	\$0	N/A		
	19-22.9 GPM (System #1 or #2) 3400 PSI max	04F	\$0	\$0		
	23-26.9 GPM (System #1 or #2) 3400 PSI max	05F	\$0	\$0		
	27-29.9 GPM (System #2) 4300 PSI max	31F	\$0	\$0		
	30-33.9 GPM (System #2) 4300 PSI max	31I	\$0	\$0		
	34-37.9 GPM (System #2) 4300 PSI max	31B	\$0	\$0		
	38-43.9 GPM (System #2) 4300 PSI max	31G	\$0	\$0		

PRODUCT CODE				\$	TOTAL LIST PRICE
GROUP	1	2	3		

	Crating Charge (Net Price)	\$200	\$250
--	-----------------------------------	-------	-------

NOTE: Hoses are included. **Couplers are NOT included.**
 System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required
 System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 120,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

