

# FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC

**LOFTNESS** 

**flail**  **HYDRO**  
**MOWER**

## FEATURES

### *Flail Mowers for Skid Steers*

- **NEW** - High Pressure Gear-Type Motor
- 26-43 GPM up to 4300 PSI
- Standard Gear Motor (With or Without Case Drain)
- 13-26 GPM up to 3400 PSI
- **Heavy-Duty, Bearing Block**
- 3-Groove Banded Belt
- **0 - 4 1/2 Inch Cutting Height** (Roller Adjustment)
- 1/4 Inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 Inch Bearing on Gauge Roller
- 1900-2200 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-Loaded Belt Tightener
- Full-Width Gauge Roller w/Roller Scraper
- Fine-Cut, Reversible Knives
- 1 3/4 Inch Rotor Bearings
- 10 Gauge Hood
- **Easy Access** Vented Belt Shield
- Hoses Are Included (Couplers Are Not)

**(800)828-7624 / (320)848-6266****LOFTNESS.COM****BUILD  
& PRICE**

650 South Main Street | Hector, MN 55342



|              |  |           |           |
|--------------|--|-----------|-----------|
| <b>SPECS</b> | Width of Cut in Inches   | <b>72</b> | <b>90</b> |
|              | Overall Width in Inches  | 84        | 102       |
|              | Number of Knives HP Required                                     | 96        | 120       |
|              | Weight in Pounds   | 1008      | 1208      |
|              | Crated Weight in Pounds  | 1275      | 1475      |
|              | Max Hydraulic Pressure (PSI) - Standard Gear Motor               | 3400      | 3400      |
|              | Max Hydraulic Pressure (PSI) - High Pressure Gear Motor          | 4300      | 4300      |
|              | Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714) | 90        | 90        |

| <b>GROUP</b>   |  | Circle/select 1 item from each group in the proper size/model column and product code column. → |           |           |
|--|--|---|-----------|-----------|
|  |  | <b>PRODUCT CODE</b>   | <b>72</b> | <b>90</b> |
| <b>Size</b>  |  |   |           |           |
| <b>1</b>   | 72 Inches                                  | <b>72HM</b>   | \$8,391   |           |
|  | 90 Inches                                  | <b>90HM</b>   |           | \$9,031   |
| <b>Hydraulic System</b>                                    |  |   |           |           |
| <b>2</b>   | #1 - No Case Drain                         | <b>1</b>  | \$3,090   | \$3,090   |
|  | #2 - With Case Drain                       | <b>2</b>  | \$2,400   | \$2,400   |
| <b>Auxiliary Hydraulic Flow (GPM) &amp; Pressure (PSI)</b> |  |   |           |           |
| <b>3</b>   | 13-15.9 GPM (System #1) 3400 PSI max       | <b>02F</b>  | \$0       | N/A       |
|  | 16-18.9 GPM (System #1) 3400 PSI max       | <b>03F</b>  | \$0       | N/A       |
|  | 19-22.9 GPM (System #1 or #2) 3400 PSI max | <b>04F</b>  | \$0       | \$0       |
|  | 23-26.9 GPM (System #1 or #2) 3400 PSI max | <b>05F</b>  | \$0       | \$0       |
|  | 27-29.9 GPM (System #2) 4300 PSI max       | <b>31F</b>  | \$0       | \$0       |
|  | 30-33.9 GPM (System #2) 4300 PSI max       | <b>31I</b>  | \$0       | \$0       |
|  | 34-37.9 GPM (System #2) 4300 PSI max       | <b>31B</b>  | \$0       | \$0       |
|  | 38-43.9 GPM (System #2) 4300 PSI max       | <b>31G</b>  | \$0       | \$0       |

|                     |                      |                      |                      |                                      |
|---------------------|----------------------|----------------------|----------------------|--------------------------------------|
| <b>PRODUCT CODE</b> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <b>\$</b><br><b>TOTAL LIST PRICE</b> |
|                     | <b>GROUP</b>         | 1                    | 2                    |                                      |

NOTE: Hoses are included. **Couplers are NOT included.**  
 System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required  
 System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

**Related Products** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 120,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**



USD - FOB Factory - Uncrated - Prices Effective 4/1/21 (Subject to Change)  
 650 South Main Street | Hector, MN 55342