

FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC

LOFTNESS 

flail  **HYDRO**
MOWER

FEATURES

*Flail Mowers for **Skid Steers***

- **NEW** - High Pressure Gear-Type Motor
- 26-43 GPM up to 4300 PSI
- Standard Gear Motor (With or Without Case Drain)
- 13-26 GPM up to 3400 PSI
- **Heavy-Duty, Bearing Block**
- 3-Groove Banded Belt
- **0 - 4 1/2 Inch Cutting Height** (Roller Adjustment)
- 1/4 Inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 Inch Bearing on Gauge Roller
- 1900-2200 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-Loaded Belt Tightener
- Full-Width Gauge Roller w/Roller Scraper
- Fine-Cut, Reversible Knives
- 1 3/4 Inch Rotor Bearings
- 10 Gauge Hood
- **Easy Access** Vented Belt Shield
- Hoses Are Included (Couplers Are Not)

(800)828-7624 / (320)848-6266**LOFTNESS.COM****BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	72	90
	Overall Width in Inches	84	102
	Number of Knives	96	120
	Weight in Pounds	1008	1208
	Crated Weight in Pounds	1275	1475
	Max Hydraulic Pressure (PSI) - Standard Gear Motor	3400	3400
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor	4300	4300
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column. →			PRODUCT CODE	72	90
Size							
1	72 Inches		72HM	\$9,121			
	90 Inches		90HM			\$9,821	
Hydraulic System							
2	#1 - No Case Drain		1	\$3,360	\$3,360		
	#2 - With Case Drain		2	\$2,610	\$2,610		
Auxiliary Hydraulic Flow (GPM) & Pressure (PSI)							
3	13-15.9 GPM (System #1) 3400 PSI max		02F	\$0	N/A		
	16-18.9 GPM (System #1) 3400 PSI max		03F	\$0	N/A		
	19-22.9 GPM (System #1 or #2) 3400 PSI max		04F	\$0	\$0		
	23-26.9 GPM (System #1 or #2) 3400 PSI max		05F	\$0	\$0		
	27-29.9 GPM (System #2) 4300 PSI max		31F	\$0	\$0		
	30-33.9 GPM (System #2) 4300 PSI max		31I	\$0	\$0		
	34-37.9 GPM (System #2) 4300 PSI max		31B	\$0	\$0		
	38-43.9 GPM (System #2) 4300 PSI max		31G	\$0	\$0		

PRODUCT CODE				\$	TOTAL LIST PRICE
	GROUP	1	2		

NOTE: Hoses are included. **Couplers are NOT included.**
 System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required
 System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

