

TIMBER AX

SKID STEER MULCHING HEAD



FEATURES

Timber Ax Forestry Mulching Heads for Skid Steers

- High Pressure Gear-Type Motor
- 22-40 GPM up to 4300 PSI - 85 Hyd. HP Max
- **Upward Rotation of Knives**
- **Adjustable Shear Bar**
- **Special Alloy, Sharpened Blades**
- Rigid, Pocket-Style Knife Mounts
- Dual Cross-Over Relief Protection
- Heavy-Duty, Bearing Block
- 2 3/16 Inch Rotor Bearings
- Bearing Anti-Wrap Protection
- 1700 RPM - 17 Inch Diameter Rotor
- 4-Groove Banded Belt
- Spring-Loaded Belt Tensioner
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Skid Shoes - Adjustable 1 to 3 Inches
- Pressure Gauge to Monitor Capacity
- Steel Deflector Chains
- Fast Rotor Shutdown
- Hoses & Hose Holder Are Included

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	73
	Overall Width in Inches	91.5
	Number of Knives	16
	Weight in Pounds	2416
	Crated Weight in Pounds	2775
	Hydraulic Horsepower Range (Hydraulic Horsepower = GPM x PSI / 1714)	40-85
	Max Hydraulic Pressure in PSI	4300

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	73
1	Size			
	73 Inches		73TA	\$23,441
2	Auxiliary Hydraulic Flow (GPM)			
	22-25.9 GPM		MP	\$0
	26-30.9 GPM		MQ	\$0
	31-36.9 GPM		MR	\$0
	37-40.9 GPM		MS	\$0

PRODUCT CODE	73TA	»	\$
GROUP	1	2	TOTAL LIST PRICE

Crating Charge (Net Price)	\$265
----------------------------	-------

NOTE: Generic hoses are included. **Couplers are NOT included.**

*Hoses: 3/4" x 108" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Patent #6,871,485

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

