## TIMBER AX SKID STEER MUI CHING HEAD







## **FEATURES**

## Timber Ax Forestry Mulching Heads for Skid Steers

- High Pressure Gear-Type Motor
- 22-40 GPM up to 4300 PSI 85 Hyd. HP Max
- Upward Rotation of Knives
- Adjustable Shear Bar
- Special Alloy, Sharpened Blades
- Rigid, Pocket-Style Knife Mounts
- Dual Cross-Over Relief Protection
- Heavy-Duty, Bearing Block
- 2 3/16 Inch Rotor Bearings
- Bearing Anti-Wrap Protection

- 1700 RPM 17 Inch Diameter Rotor
- 4-Groove Banded Belt
- Spring-Loaded Belt Tensioner
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Skid Shoes Adjustable 1 to 3 Inches
- Pressure Gauge to Monitor Capacity
- Steel Deflector Chains
- Fast Rotor Shutdown
- Hoses & Hose Holder Are Included

BUILD & PRICE

## **TIMBER AX**

	Width of Cut in Inches	73
	Overall Width in Inches	91.5
(0	Number of Knives	16
SPECS	Weight in Pounds	2416
S	Crated Weight in Pounds	2775
	Hydraulic Horsepower Range (Hydraulic Horsepower = GPM x PSI / 1714)	40-85
	Max Hydraulic Pressure in PSI	4300

GROUP		select 1 item from each group in the proper odel column and product code column.	PRODUCT CODE	73	
	Size				
1	73 Inches		73TA	\$26,341	
	Auxilary Hydraulic Flow (GPM)				
	22-25.9 GPM		MP	\$0	
2	26-30.9 GPM		MQ	\$0	
	31-36.9 GPM		MR	\$0	
	37-40.9 GPM		MS	\$0	

PRODUCT CODE	73TA	<b>»</b>	\$
GROUP	1	2	TOTAL LIST PRICE

NOTE: Generic hoses are included. Couplers are NOT included.

\*Hoses: 3/4" x 108" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Patent #6,871,485

**Related** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With **Products** Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

