

# CARBIDE CUTTER G4

SKID STEER MULCHING HEAD



carbide **G4**  
CUTTER



## FEATURES

### Forestry Mulching Heads for *Skid Steers*

- Choose From 3 Tooth Designs - Ultra-Sharp Quadco Reversible Knives, Quadco Hard-Surfaced or Rugged Double Carbide Teeth
- **Two-Stage Cutting Chamber** - 2 Shear Bars Producing a Finer Mulch With Less Passes
- Variable Disp. Piston-Type Motor 90-110 cc
- Fixed Disp. High Pressure Gear-Type Motor
- Heavy-Duty Bearing Block
- Re-Cutter Bar at Discharge
- **Adjustable Bolt-In 2nd Shear Bar**
- Machined Bearing Anti-Wrap
- **Efficient Staggered Carbide Tooth Pattern**
- Premium Strength Steel Housing
- Increased Visibility
- 1600-2000 Rotor RPM
- 17 Inch Diameter Rotor
- 2-3/16" Piloted Double Taper Roller Bearings
- Synchronous Belt
- On-Board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Adjustable Skid Shoes -1.5 to +0.5 Inches
- Hoses Are Included (No Couplers)
- Adjustable Tree-Pusher Bar
- Universal Skid-Steer Mount
- Welded Claw Hooks on Pusher Bar
- Improved Hose Routing

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD  
& PRICE

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches		<b>61</b>	<b>71</b>	
	Overall Width in Inches		76.2	86.2	
	Number of Teeth		36	42	
	Weight in Pounds		2505	2706	
	Crated Weight in Pounds		2725	2925	
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	61	71
	<b>Size</b>				
1	61 Inches		<b>61G4</b>	\$18,715	
	71 Inches		<b>71G4</b>		\$19,825
	<b>Teeth</b>				
2	Standard Double Carbide - N15510 (\$80.00 ea.)		<b>S</b>	\$2,940	\$3,430
	Quadco Reversible Knives - N24279 (\$37.00 ea.)		<b>Q</b>	\$3,120	\$3,650
	Hard-surfaced Quadco Reversible Knives - 200011 (\$57.00 ea.)		<b>H</b>	\$3,840	\$4,490
	<b>Hydraulic Motor (Hydraulic Horsepower = GPM x PSI / 1714)</b>				
3	Variable Displacement Piston Motor - 50-120 Hydraulic Horsepower*		<b>44</b>	\$8,650	\$8,650
	Fixed Disp. High Pressure Gear Motor - 50-85 Hydraulic Horsepower**		<b>38</b>	\$3,650	\$3,650
	<b>Auxiliary Hydraulic Flow (GPM)</b>				
4	33-37.9 GPM (Variable Disp. Motor) up to 6000 PSI		<b>A</b>	\$0	\$0
	38-41.9 GPM (Variable Disp. Motor) up to 6000 PSI		<b>B</b>	\$0	\$0
	42-45.9 GPM (Variable Disp. Motor) up to 6000 PSI		<b>D</b>	\$0	\$0
	28-30.9 GPM (Fixed Disp. Motor) up to 4300 PSI		<b>E</b>	\$0	\$0
	31-35.9 GPM (Fixed Disp. Motor) up to 4300 PSI		<b>F</b>	\$0	\$0
	36-40.9 GPM (Fixed Disp. Motor) up to 4300 PSI		<b>G</b>	\$0	\$0
	<b>Auxiliary Hydraulic Pressure (psi)</b>				
5	Fixed Displacement High Pressure Gear Motor		<b>0</b>	\$0	\$0
	2800-3499 PSI (Variable Displacement Motor System)		<b>1</b>	\$0	\$0
	3500-3899 PSI (Variable Displacement Motor System)		<b>2</b>	\$0	\$0
	3900-4400 PSI (Variable Displacement Motor System)		<b>3</b>	\$0	\$0
	<b>OPTIONS</b>				
OPTIONS	Right Hand Hose Conversion Kit, 6000 PSI (207088) (Variable Disp. Motor)		<b>V</b>	\$580	\$580
	Right Hand Hose Conversion Kit, 4000 PSI (207808) (Fixed Disp. Motor)		<b>F</b>	\$380	\$380

PRODUCT CODE							<div style="text-align: center;">\$</div> <b>TOTAL LIST PRICE</b>
	GROUP	1	2	3	4	5	

Crating Charge (Net Price)	\$250	\$250
----------------------------	-------	-------

NOTE: Hoses are included. **Couplers are NOT included.**

\*Variable Motor: 1" with -16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

\*\*Fixed Motor: 3/4" with -12 MORB Male O-ring, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**



USD - FOB Factory - Uncrated - Prices Effective 4/1/21 (Subject to Change)

650 South Main Street | Hector, MN 55342