

BATTLE AX - 20 SERIES

EXCAVATOR MULCHING HEAD



FEATURES

Forestry Mulching Heads for **10,000-20,000 lb Excavators**

- “Battle Ax” Rotor Design - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Two Tooth Designs** - 4 Point Beaver Teeth or Ultra Sharp Reversible Planer
- 40cc Fixed Displacement Gear Motor
- 3 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 20-70 Hydraulic HP (15-35 GPM @ up to 4100 PSI)
- Optional Spade Hook - With Optional Hydraulic Thumb
- Standard Flat Plate Mount / Included in Base Price
- Optional Mounts - Direct, Quick Attach or Pivoting
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 2000-2600 RPM
- Steel Deflector Chains
- With or Without Case Drain

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD
& PRICE



650 South Main Street | Hector, MN 55342

SPECS	Width of Cut in Inches	31	41	51
	Recommended Excavator Weight Range (in Pounds)	10K-15K	15K-20K	15K-20K
	Overall Width in Inches	46.25	56.25	66.25
	Number of Teeth	20	26	32
	Weight Without Mount in Pounds	879	1084	1218
	Crated Weight in Pounds	978	1183	1317
	Hydraulic Horsepower Required (Hydraulic HP = GPM X PSI/1714)	20-70	25-70	25-70

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	31	41	51
Size					
1	31 Inches	31BX20	\$16,321		
	41 Inches	41BX20		\$17,311	
	51 Inches	51BX20			\$18,111
Teeth					
2	Quadco 4 Point Beaver Teeth - N156042 (\$20.00 ea.)	Q	\$400	\$520	\$640
	Quadco Reversible Planer Teeth - 202970 (\$25.00 ea.)	P	\$500	\$650	\$800
Hydraulic Motor					
3	Gear Motor - 40cc 15-35 GPM up to 4100 PSI (Use with or without Case Drain*)	52	Included	Included	Included
Belt Drive Combination					
4	15-19.9 GPM	A	Included	Included	Included
	20-23.9 GPM	B	Included	Included	Included
	24-27.9 GPM	C	Included	Included	Included
	28-31.9 GPM	D	Included	Included	Included
	32-34.9 GPM	E	Included	Included	Included
OPTIONS					
OPTIONS	Spade Hook	H	\$150	\$150	\$150
	Thumb Attachment (Requires Spade Hook)	T	\$790	\$790	\$790
	Mount - EXTRA Blank Plate Mount (1 Included in Base Price)	N49170	\$220	\$220	\$220
	Mount - Custom Mount Without Pins (Need to Specify Quick Attach or Pin-On)		\$1,450	\$1,450	\$1,450

PRODUCT CODE	<input type="text"/>	»	<input type="text"/>	»	<input type="text"/>	»	<input type="text"/>	»	<input type="text"/>	\$	TOTAL LIST PRICE
GROUP	1		2		3		4		OPTIONS		

NOTE: **Hoses and Couplers from Power Unit to Head Are NOT Included.**

*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD & PRICE



USD - FOB Factory - Uncrated - Prices Effective 4/1/21 (Subject to Change)

650 South Main Street | Hector, MN 55342