

BATTLE AX - H SERIES

SKID STEER MULCHING HEAD

LOFTNESS 

AN EMPLOYEE OWNED COMPANY

battle 

AX Skid-Steer



FEATURES

*Forestry Mulching Heads for **Skid Steers***

- "Battle Ax" Rotor Design - Uses Built-In Depth Gauges to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - Uses 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- Choose From 3 Tooth Designs - Reversible Planer Knives, Hard-Surfaced Planer or Double Carbide
- Variable Displacement Piston-Type Motor 90-110 CC
- Adjustable Primary Shear Bar
- Premium Strength Steel Housing
- 1600-2300 Rotor RPM
- 17 Inch Diameter Rotor
- 2-1/2" Piloted Double Taper Roller Bearings
- Machined Bearing Anti-Wrap
- Synchronous Belt Drive
- On Board PSI Gauge to Monitor Capacity
- 1" Wall Rotor Tube
- Adjustable Skid Shoes -1.5 to +0.5 Inches
- Manual or Hydraulic Pusher Bar
- Welded Claw Hooks on Pusher Bar
- Optional Universal Skid Steer Mount
- Optional Custom Mounts Available

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



2022 RETAIL PRICING

BATTLE AX - H SERIES

SPECS	Cutting Width in Inches	88
	Overall Width in Inches	101.50
	Number of Teeth	44
	Weight in Pounds	3816
	Crated Weight in Pounds	3990
	Required Hydraulic HP	90-150HP

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	88
1	Size		
	88 Inches	88BH	\$32,752
2	Teeth		
	Quadco Reversible Knives - N49366 (\$41.00 each)	Q	\$1,800
	Hard-Surfaced Quadco Reversible Knives - 203014 (\$61.00 each)	H	\$2,680
	Standard Double Carbide - N49090 (\$75.00 each)	S	\$3,300
3	Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)		
	Variable Displacement Piston Motor (Closed Loop)	41	\$11,610
	Variable Displacement Piston Motor (Open Loop)	48	\$11,140
4	Auxiliary Hydraulic Flow (GPM)		
	33-37.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	A	\$0
	38-42.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	B	\$0
	43-47.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	D	\$0
	48-52.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	H	\$0
	53-57.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	I	\$0
	58-62.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	J	\$0
	33-37.9 (Variable Disp. Motor) - up to 6000PSI High Speed	T	\$0
	38-42.9 (Variable Disp. Motor) - up to 6000PSI High Speed	U	\$0
	43-47.9 (Variable Disp. Motor) - up to 6000PSI High Speed	V	\$0
	48-52.9 (Variable Disp. Motor) - up to 6000PSI High Speed	D	\$0
	53-57.9 (Variable Disp. Motor) - up to 6000PSI High Speed	H	\$0
	58-62.9 (Variable Disp. Motor) - up to 6000PSI High Speed	I	\$0
	5	Auxiliary Hydraulic Pressure (PSI)	
2800-3499 PSI		1	\$0
3500-3899 PSI		2	\$0
3900-4399 PSI		3	\$0
4400-5099 PSI		4	\$0
5100-5999 PSI		5	\$0
OPTIONS	Universal Skid Mount	S	\$1,040
	Pusher, Hydraulic	H	\$2,160

PRODUCT CODE	▶▶▶▶▶▶▶▶	\$	TOTAL LIST PRICE
GROUP	1 2 3 4 5 OPTIONS		

NOTE: Hoses and couplers are NOT included.

(800)828-7624 / (320)848-6266

LOFTNESS.COM



USD - FOB Factory - Uncrated - Prices Effective 3/1/22 (Subject to Change)

650 South Main Street | Hector, MN 55342

L10084 - 4/26/22