

# FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC

**LOFTNESS**  
AN EMPLOYEE OWNED COMPANY



**flail** HYDRO  
**MOWER**

## FEATURES

### *Flail Mowers for **Skid Steers***

- High Pressure Gear-Type Motor
- 26-43 GPM up to 4300 PSI
- Standard Gear Motor (With or Without Case Drain)
- 13-26 GPM up to 3400 PSI
- **Heavy-Duty, Bearing Block**
- 3-Groove Banded Belt
- **0 - 4 1/2 Inch Cutting Height** (Roller Adjustment)
- 1/4 Inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 Inch Bearing on Gauge Roller
- 1900-2200 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-Loaded Belt Tightener
- Full-Width Gauge Roller w/Roller Scraper
- Fine-Cut, Reversible Knives
- 1 3/4 Inch Rotor Bearings
- 10 Gauge Hood
- **Easy Access** Vented Belt Shield
- Hoses Are Included (Couplers Are Not)

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

**BUILD  
& PRICE**

650 South Main Street | Hector, MN 55342



<b>SPECS</b>	Width of Cut in Inches	<b>72</b>	<b>90</b>
	Overall Width in Inches	84	102
	Number of Knives	96	120
	Weight in Pounds	1,008	1,208
	Max Hydraulic Pressure (PSI) - Standard Gear Motor	3,400	3,400
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor	4,300	4,300
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

<b>GROUP</b>		Circle/select 1 item from each group in the proper size/model column and product code column. →		<b>PRODUCT CODE</b>	<b>72</b>	<b>90</b>
<b>Size</b>						
<b>1</b>	72 Inches	<b>72HM</b>	\$10,943			
	90 Inches	<b>90HM</b>				\$11,793
<b>Hydraulic System</b>						
<b>2</b>	#1 - No Case Drain	<b>1</b>	\$4,020		\$4,020	
	#2 - With Case Drain	<b>2</b>	\$3,130		\$3,130	
<b>Auxiliary Hydraulic Flow (GPM) &amp; Pressure (PSI)</b>						
<b>3</b>	13-15.9 GPM (System #1) 3400 PSI max	<b>02F</b>	\$0			N/A
	16-18.9 GPM (System #1) 3400 PSI max	<b>03F</b>	\$0			N/A
	19-22.9 GPM (System #1 or #2) 3400 PSI max	<b>04F</b>	\$0			\$0
	23-26.9 GPM (System #1 or #2) 3400 PSI max	<b>05F</b>	\$0			\$0
	27-29.9 GPM (System #2) 4300 PSI max	<b>31F</b>	\$0			\$0
	30-33.9 GPM (System #2) 4300 PSI max	<b>31I</b>	\$0			\$0
	34-37.9 GPM (System #2) 4300 PSI max	<b>31B</b>	\$0			\$0
	38-43.9 GPM (System #2) 4300 PSI max	<b>31G</b>	\$0			\$0

<b>PRODUCT CODE</b>		»		»		<b>\$</b>	
	<b>GROUP</b>	<b>1</b>		<b>2</b>			<b>3</b>

NOTE: Hoses are included. **Couplers are NOT included.**  
 System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required  
 System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

**Related Products** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

