



For Tractors With 540 or 1,000 RPM PTO and 50-250 Horsepower

SPECIFICATI					
	18" or 20" (45.7 cm or 50.8 cm)	Impeller Diameter	62.5" (158.8 cm)	Length	6
	3-point Cat II or III quick hitch	Mount	47.75" (121.3 cm)	Height	
	PTO driven, belt drive	Drive	51.5" (130.8 cm)	Width	
	Reversible, hardened	Blades	985 lbs (447 kg)	Weight	
	Ratchet adjust	Skid Shoes	30' (9.1 m)	Soil Spread	
SNOI	50-250 HP	HP Range	12" (30.5 cm)	Maximum Depth	

// The Best Way to Dig a Ditch

Improve drainage in ditches, fields and many other applications with the Loftness Ditcher. Heavy-duty construction, easy operation and adjustable performance make Loftness a superior choice for water control.





// DITCHER FEATURES



Adjustable Skid Shoes:

The skid shoes allow the cutting depth to be adjusted up to 12 inches deep. A ratchet link provides easy and precise adjustment.



30-Foot Spread Distance:

The powerful impellers are capable of spreading soil up to 30-foot (9.1 m) distances.



Belt Drive:

A 5-band belt drive with taper-lock sheaves provides reliable, efficient transfer of power from the tractor to the impeller. The belt has a spring tensioner with an easy nut adjustment.




Adjustable Impeller Blades:

The impeller blades are adjustable, allowing you to dig 18- or 20-inch-wide ditches. The blades are also reversible to double the service life before replacement is needed.



Point Shank:

A point shank breaks up soil ahead of the impeller. It is designed for running in hard or rocky conditions.



Jack Stands: The included jack stands allow the Ditcher to be easily hooked up and disconnected.

SEE THE FULL LIST OF FEATURES AND SPECS AT **LOFTNESS.COM**



EQUIPMENT FROM LOFTNESS



GRAIN BAGGING



CROP SHREDDERS



VEGETATION MANAGEMENT

// GRAIN BAGGING

Call us or ask your local Loftness

dealer about the Loftness Ditcher.

// CROP SHREDDERS

// VEGETATION MANAGEMENT

// FERTILIZER EQUIPMENT



FERTILIZER EQUIPMENT

Loftness Specialized Equipment, Inc. P.O. Box 337 Hector, Minnesota 55342 USA

Toll Free US & Canada: 800-828-7624 International 320-848-6266 email: info@loftness.com www.loftness.com