

BATTLE AX - 30 SERIES

EXCAVATOR MULCHING HEAD

LOFTNESS
AN EMPLOYEE OWNED COMPANY

battle 
AX Excavator



FEATURES

Forestry Mulching Heads for **18,000-36,000 lb Excavators**

- **“Battle Ax” Rotor Design** - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - Reversible Planer, Hard Surface Planer or Double Carbide
- 105cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 45-150 Hydraulic HP (20-60 GPM @ up to 6000 PSI)
- Optional Spade Hook - With Optional Hydraulic Thumb
- Optional Mounts - Blank, Pin-On, Pin Grabber or Tilt Hitch
- 17 in (43.2 cm) Diameter Rotor
- 2 3/16 in (55.56 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1800-2500 RPM
- Steel Deflector Chains
- 37 mm Synchronous Belt
- **Optional Tilt Hitch** - Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**



650 South Main Street | Hector, MN 55342

SPECS	Width of Cut in Inches	41	51
	Recommended Excavator Weight Range (in Pounds)	18K-36K	18K-36K
	Overall Width in Inches	56.375	66.375
	Number of Teeth	20	26
	Weight Without Mount in Pounds	2,010	2,210
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	45-150	45-150
	Hydraulic Flow Range (GPM)	20-60	20-60

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	41	51
Size					
1	41 Inches		41BX30	\$33,603	
	51 Inches		51BX30		\$35,203
Teeth					
2	Reversible Planer Teeth p/n N49366 (\$41.00 ea.)		Q	\$820	\$1,070
	Reversible Planer Hard p/n 203014 (\$61.00 ea.)		H	\$1,220	\$1,590
	Double Carbide Teeth p/n N49090 (\$75.00 ea.)		S	\$1,500	\$1,950
Hydraulic Motor					
3	Piston Motor - 105cc 20-60 GPM up to 6000 PSI - Case Drain Required		57	Included	Included
Belt Drive Combination					
4	20-60 GPM		A	Included	Included
OPTIONS					
5	Spade Hook		H	\$190	\$190
	Thumb Attachment (Requires Spade Hook)		T	\$1,030	\$1,030
Mount					
5	Blank Plate Mount		N49170	\$290	\$290
	Common Factory/OEM Specific Mount			\$2,200	\$2,200
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)			\$2,200	\$2,200
	Custom Mount, Pin Grabber Style (Welded Pins)			\$1,550	\$1,550
	Tilt Hitch with Blank Plate Mount (Requires AUX Connection)			\$2,490	\$2,490
	Tilt Hitch with Common Factory/OEM Specific Mount			\$4,400	\$4,400
	Tilt Hitch with Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin) (Requires AUX Connection)			\$4,400	\$4,400
	Tilt Hitch with Custom Mount, Pin Grabber Style (Welded Pins) (Requires AUX Connection.)			\$3,750	\$3,750
	Special Aftermarket Mount (Call for Pricing and Availability)			CALL	CALL

PRODUCT CODE	1	2	3	4	OPTIONS	5	\$	TOTAL LIST PRICE
	1	2	3	4	OPTIONS	5		

NOTE: Hoses and couplers from Power Unit to Head Are NOT Included. Case Drain Required.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD & PRICE

