BATTLE AX - 40 SERIES EXCAVATOR MULCHING HEAD

AN EMPLOYEE OWNED COMPANY





FEATURES

Forestry Mulching Heads for 36,000-60,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs Reversible Planer, Hard Surface Planer or Double Carbide
- 135cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar

- Power Requirement 80-210 Hydraulic HP (25-75 GPM @ up to 6000 PSI)
- Optional Spade Hook
- 17 in (43.2 cm) Diameter Rotor
- 2 1/2 in (63.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1800-2500 RPM
- Steel Deflector Chains
- 68 mm Synchronous Belt
- Optional Mounts Pin-On or Pin Grabber





2024 RETAIL PRICING

BATTLE AX - 40 SERIES

SPECS	Width of Cut in Inches	51
	Recommended Excavator Weight Range (in Pounds)	36K-60K
	Overall Width in Inches	80.6
	Number of Teeth	26
	Weight Without Mount in Pounds	3,010
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	80-210
	Hydraulic Flow Range (GPM)	25-75

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column.	PRODUCT CODE	51	
1	Size			
	51 Inches Standard-Duty	51BX40	\$55,173	
	Teeth			
2	Quadco Reversible Planer Teeth - N49366 (\$41.00 ea.)	Q	\$1,070	
2	Hard-surfaced Quadco Knives - 203014 (\$61.00 ea.)	Н	\$1,590	
	Double Carbide - N49090 (\$75.00 ea.)	S	\$1,950	
3	Hydraulic Motor			
J	Piston Motor - 135cc 25-75 GPM up to 6000 PSI (Case Drain Required)	51	Included	
4	Belt Drive Combination			
4	25-75 GPM	Α	Included	
OPTIONS	Spade Hook	н	\$530	
	Mount			
	Common Factory/OEM Specific Mount		\$3,450	
5	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)		\$3,450	
	Custom Mount, Pin Grabber Style (Welded Pins)		\$2,600	
	Special Aftermarket Mount (Call for Pricing and Availability)		CALL	



(800)828-7624 / (320)848-6266

