

# BATTLE AX - S SERIES

## SKID STEER MULCHING HEAD

**LOFTNESS**   
AN EMPLOYEE-OWNED COMPANY



## FEATURES

### *Forestry Mulching Heads for **Skid Steers***

- **“Battle Ax” Rotor Design** - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Less Passes
- **Three Tooth Designs** - Reversible Planer Knives, Hard-Surfaced Planer or Double Carbide Teeth
- Variable Disp. Piston-type Motor 90-110 cc
- Fixed Disp. High Pressure Gear-Type Motor
- **GPM Rating** 28-62.9 GPM
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Adjustable Tree-Pusher Bar
- Welded Claw Hooks on Pusher Bar
- 17 Inch Diameter Rotor
- 2-3/16" Piloted Double Taper Roller Bearings
- Machined Bearing Anti-Wrap
- Rotor Speed 1600-2300 RPM
- Synchronous Belt Drive
- On-Board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Replaceable Skid Shoes
- Hoses Are Included (No Couplers)
- Improved Hose Routing
- Universal Skid Steer Mount
- Optional Bolt-in Liner
- Increased Visibility

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

**BUILD  
& PRICE**



650 South Main Street | Hector, MN 55342

<b>SPECS</b>	Width of Cut in Inches	<b>61</b>	<b>71</b>
	Overall Width in Inches	79.1	89.1
	Number of Teeth	30	36
	Weight in Pounds	2,604	2,841

<b>GROUP</b>		Circle/select 1 item from each group in the proper size/model column and product code column. →	<b>PRODUCT CODE</b>	<b>61</b>	<b>71</b>
<b>1</b>	<b>Size</b>				
	61 Inches		<b>61BS</b>	\$28,013	
	71 Inches		<b>71BS</b>		\$29,603
<b>2</b>	<b>Teeth</b>				
	Quadco Reversible Knives - N49366 (\$41.00 ea.)		<b>Q</b>	\$1,230	\$1,480
	Hard-surfaced Quadco Reversible Knives - 203014 (\$61.00 ea.)		<b>H</b>	\$1,830	\$2,200
	Standard Double Carbide - N49090 (\$75.00 ea.)		<b>S</b>	\$2,250	\$2,700
<b>3</b>	<b>Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)</b>				
	Variable Displacement Piston Motor - (Closed Loop) 50-150 Hydraulic Horsepower*		<b>45</b>	\$12,620	\$12,620
	Variable Displacement Piston Motor - (Open Loop) 50-150 Hydraulic Horsepower*		<b>44</b>	\$12,110	\$12,110
	Fixed Disp. High Pressure Gear Motor - 50-85 Hydraulic Horsepower**		<b>38</b>	\$5,110	\$5,110
<b>4</b>	<b>Auxiliary Hydraulic Flow (GPM)</b>				
	28-32.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>T</b>	\$0	\$0
	33-37.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>A</b>	\$0	\$0
	38-42.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>B</b>	\$0	\$0
	43-47.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>D</b>	\$0	\$0
	48-52.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>H</b>	\$0	\$0
	53-57.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>I</b>	\$0	\$0
	58-62.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed		<b>J</b>	\$0	\$0
	32-37.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>T</b>	\$0	\$0
	38-41.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>U</b>	\$0	\$0
	42-47.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>V</b>	\$0	\$0
	48-52.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>D</b>	\$0	\$0
	53-57.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>H</b>	\$0	\$0
	58-62.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option		<b>I</b>	\$0	\$0
	28-30.9 GPM (Fixed Disp. Motor) - up to 4300 PSI		<b>E</b>	\$0	\$0
	31-35.9 GPM (Fixed Disp. Motor) - up to 4300 PSI		<b>F</b>	\$0	\$0
	36-40.9 GPM (Fixed Disp. Motor) - up to 4300 PSI		<b>G</b>	\$0	\$0
<b>5</b>	<b>Auxiliary Hydraulic Pressure (PSI)</b>				
	Fixed Displacement High Pressure Gear Motor		<b>0</b>	\$0	\$0
	2800-3499 PSI - (Variable Displacement Motor System)		<b>1</b>	\$0	\$0
	3500-3899 PSI - (Variable Displacement Motor System)		<b>2</b>	\$0	\$0
	3900-4399 PSI - (Variable Displacement Motor System)		<b>3</b>	\$0	\$0
	4400-5099 PSI - (Variable Displacement Motor System)		<b>4</b>	\$0	\$0
	5100-5999 PSI - (Variable Displacement Motor System)		<b>5</b>	\$0	\$0
<b>OPTIONS</b>	Right Hand Hose Conversion Kit, 6000 PSI (209064) (Variable Disp. Motor)		<b>V</b>	\$750	\$750
	Right Hand Hose Conversion Kit, 4000 PSI (209065) (Fixed Disp. Motor)		<b>F</b>	\$490	\$490
	Bolt-in Liner (61BS - 209043) (71BS - 209044)		<b>L</b>	\$860	\$910

<b>PRODUCT CODE</b>								<b>\$</b>
<b>GROUP</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>OPTIONS</b>		<b>TOTAL LIST PRICE</b>

NOTE: Hoses are included. Couplers are NOT included.

\*Variable Motor: 1" with -16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

\*\*Fixed Motor: 3/4" with -12 MORB Male O-ring, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

**BUILD & PRICE**



USD - FOB Factory - Uncrated - Prices Effective 2/21/24 (Subject to Change)

650 South Main Street | Hector, MN 55342