

BATTLE AX TRACTOR

TRACTOR MOUNT MULCHING HEAD

LOFTNESS 
AN EMPLOYEE-OWNED COMPANY



FEATURES

Forestry Mulching Heads for Tractors

- **“Battle Ax” Rotor Design** – Uses Built-in “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - Uses 2 Shear Bars, Producing a Finer Mulch with Fewer Passes
- 61" Cutting Width
- **Three Tooth Designs** – 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- 70 HP Gearbox & Driveline
- 540 RPM PTO Shaft
- 1-3/4" Piloted Double Taper Roller Bearings
- 13.5" Cutting Tip Diameter
- Efficient Staggered/Spiral Tooth Pattern
- Machined Bearing Anti-Wrap Design
- Premium Strength Steel Housing
- Steel Deflector Chains
- Rotor Speed 2200 RPM
- Cat. I, Adaptable to Cat. II, Free-Link or Quick Hitch
- 3-B Section Banded Belt
- Centered or 16" Offset to the Right
- Spring-Loaded Belt Tensioner
- 3/16" Hood
- 1/4" End Plates
- Optional – Manual Tree-Pusher Bar
- Optional – Containment Door
- Optional – Deflector Door

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	61
	Overall Width in Inches	76
	Number of Teeth	38
	Weight in Pounds (Includes Hydraulic Pusher)	1675
	Deflector Door Weight (Optional)	86
	Containment Door Weight (Optional)	207
	PTO Horsepower Range	30-70

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	61
1	Size			
	61 Inches (Includes fixed push bar)		61BT20	\$24,453
2	Teeth			
	Quadco 4 Point Beaver Teeth - N156042		Q	\$800
	Quadco Reversible Planer Teeth - 202970		P	\$1,030
	Double Carbide Teeth - 209036		S	\$2,470
3	PTO			
	1 - 3/8 - 6 W2400 K64/22R 540RPM		A	Included
OPTIONS	Containment Door			
			C	\$3,990
	Deflector Door			
			D	\$1,250
5	Pusher Bar			
	Manual Pusher Bar		F	\$350
	Hydraulic Pusher Bar		H	\$2,350

PRODUCT CODE		»		»		»		»		\$
GROUP	1		2		3		OPTIONS		5	TOTAL LIST PRICE

NOTE: Generic hoses are included. **Couplers are NOT included.**

