

FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC

LOFTNESS
AN EMPLOYEE-OWNED COMPANY



FEATURES

*Flail Mowers for **Skid Steers***

- High Pressure Gear-Type Motor
- 26-43 GPM up to 4300 PSI
- Standard Gear Motor (With or Without Case Drain)
- 13-26 GPM up to 3400 PSI
- **Heavy-Duty, Bearing Block**
- 3-Groove Banded Belt
- **0 - 4 1/2 Inch Cutting Height** (Roller Adjustment)
- 1/4 Inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 Inch Bearing on Gauge Roller
- 1900-2200 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-Loaded Belt Tightener
- Full-Width Gauge Roller w/Roller Scraper
- Fine-Cut, Reversible Knives
- 1 3/4 Inch Rotor Bearings
- 10 Gauge Hood
- **Easy Access** Vented Belt Shield
- Hoses Are Included (Couplers Are Not)

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

650 South Main Street | Hector, MN 55342



SPECS	Width of Cut in Inches	72	90
	Overall Width in Inches	84	102
	Number of Knives	96	120
	Weight in Pounds	1,008	1,208
	Max Hydraulic Pressure (PSI) - Standard Gear Motor	3,400	3,400
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor	4,300	4,300
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →			PRODUCT CODE	72	90
Size						
1	72 Inches	72HM	\$10,943			
	90 Inches	90HM			\$11,793	
Hydraulic System						
2	#1 - No Case Drain	1	\$4,020	\$4,020		
	#2 - With Case Drain	2	\$3,130	\$3,130		
Auxiliary Hydraulic Flow (GPM) & Pressure (PSI)						
3	13-15.9 GPM (System #1) 3400 PSI max	02F	\$0	N/A		
	16-18.9 GPM (System #1) 3400 PSI max	03F	\$0	N/A		
	19-22.9 GPM (System #1 or #2) 3400 PSI max	04F	\$0	\$0		
	23-26.9 GPM (System #1 or #2) 3400 PSI max	05F	\$0	\$0		
	27-29.9 GPM (System #2) 4300 PSI max	31F	\$0	\$0		
	30-33.9 GPM (System #2) 4300 PSI max	31I	\$0	\$0		
	34-37.9 GPM (System #2) 4300 PSI max	31B	\$0	\$0		
	38-43.9 GPM (System #2) 4300 PSI max	31G	\$0	\$0		

PRODUCT CODE	<input type="text"/>	»	<input type="text"/>	»	<input type="text"/>	\$	TOTAL LIST PRICE
GROUP	1		2		3		

NOTE: Hoses are included. **Couplers are NOT included.**
 System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required
 System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

