## TIMBER AX SKID STEER MULCHING HEAD







## **FEATURES**

## Timber Ax Forestry Mulching Heads for Skid Steers

- High Pressure Gear-Type Motor
- 22-40 GPM up to 4300 PSI 85 Hyd. HP Max
- Upward Rotation of Knives
- Adjustable Shear Bar
- Special Alloy, Sharpened Blades
- Rigid, Pocket-Style Knife Mounts
- Dual Cross-Over Relief Protection
- Heavy-Duty, Bearing Block
- 2 3/16 Inch Rotor Bearings
- Bearing Anti-Wrap Protection

- 1700 RPM 17 Inch Diameter Rotor
- 4-Groove Banded Belt
- Spring-Loaded Belt Tensioner
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Skid Shoes Adjustable 1 to 3 Inches
- Pressure Gauge to Monitor Capacity
- Steel Deflector Chains
- Fast Rotor Shutdown
- Hoses & Hose Holder Are Included

BUILD & PRICE

## **TIMBER AX**

	Width of Cut in Inches	73	83
	Overall Width in Inches	91.5	101.5
SPECS	Number of Knives	16	18
SPE	Weight in Pounds	2,416	2,632
	Hydraulic Horsepower Range (Hydraulic Horsepower = GPM x PSI / 1714)	40-85	40-85
	Max Hydraulic Pressure in PSI	4,300	4,300

GROUP	Circle/select 1 item from each group in the prope size/model column and product code column. ——		73	83
1	Size			
•	73 Inches	73TA	\$31,594	
	83 Inches	83TA		\$32,514
	Auxilary Hydraulic Flow (GPM)			
	22-25.9 GPM	MP	\$0	\$0
2	26-30.9 GPM	MQ	\$0	\$0
	31-36.9 GPM	MR	\$0	\$0
	37-40.9 GPM	MS	\$0	\$0

PRODUCT	<b>&gt;&gt;</b>	\$
GROUP 1	2	TOTAL LIST PRICE

NOTE: Generic hoses are included. Couplers are NOT included.

\*Hoses: 3/4" x 108" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Patent #6,871,485

**Related** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With **Products** Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

