

BATTLE AX® - 10 SERIES

EXCAVATOR MULCHING HEAD

LOFTNESS 


FEATURES

Forestry Mulching Heads for **7,000-10,000 lb Excavators**

- **“Battle Ax” Rotor Design** - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- 45cc Fixed Displacement Gear Motor
- 2 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 20-70 Hydraulic HP (15-19.9 GPM @ up to 4100 PSI)
- Optional Spade Hook
- Optional Mounts - Pin-On, Pin Grabber or Blank Plate
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1750-2300 RPM
- Steel Deflector Chains
- Case Drain Highly Recommended

(800)828-7624 / (320)848-6266
LOFTNESS.COM
**BUILD
& PRICE**


650 Main Street South | Hector, MN 55342

| | | |
|-------|--|-----------|
| SPECS | Width of Cut in Inches | 25 |
| | Recommended Excavator Weight Range (in Pounds) | 7K-10K |
| | Overall Width in Inches | 45 |
| | Number of Teeth | 16 |
| | Weight Without Mount (in Pounds) | 620 |
| | Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714) | 20-70 |
| | Hydraulic Flow Range (GPM) | 15-19.9 |

| GROUP | | Circle/select 1 item from each group in the proper size/model column and product code column. → | PRODUCT CODE | 25 |
|---------|--|---|--------------|----------|
| 1 | Size | | | |
| | 25 Inches | | 25BX10 | \$17,874 |
| 2 | Teeth | | | |
| | Quadco 4 Point Beaver Teeth - N156042 (\$21.00 ea.) | | Q | \$340 |
| | Quadco Reversible Planer Teeth - 202970 (\$27.00 ea.) | | P | \$440 |
| | Double Carbide Teeth - 209036 (\$65.00 ea.) | | S | \$1040 |
| 3 | Hydraulic Motor | | | |
| | Gear Motor - 45cc 15-19.9 GPM up to 4100 PSI (Use with or without Case Drain*) | | 65 | Included |
| 4 | Belt Drive Combination | | | |
| | 15-19.9 GPM | | A | Included |
| OPTIONS | OPTIONS | | | |
| | Spade Hook | | H | \$190 |
| 5 | Mount | | | |
| | Blank Plate Mount | | | \$100 |
| | Common Factory/OEM Specific Mount | | | \$950 |
| | Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.) | | | \$950 |
| | Custom Mount, Pin Grabber Style (Welded Pins) | | | \$750 |
| | Special Aftermarket Mount (Call for Pricing and Availability) | | | CALL |

| | | | | | | | | | | | |
|--------------|---|---|---|---|---|---|---|---|---------|---|---|
| PRODUCT CODE | | » | | » | | » | | » | | » | |
| GROUP | 1 | | 2 | | 3 | | 4 | | OPTIONS | | 5 |

| |
|------------------|
| \$ |
| TOTAL LIST PRICE |

NOTE: **Hoses and Couplers from Power Unit to Head Are NOT Included.**

*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**

