# BATTLE AX® - 30 SERIES

LOFTNESS
AN EMPLOYEE-OWNED COMPANY







#### **FEATURES**

### Forestry Mulching Heads for 18,000-36,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker"
   Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars,
   Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs Reversible Planer, Hard
   Surface Planer or Double Carbide
- 105cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar
- Power Requirement 45-150 Hydraulic HP
   (20-60 GPM @ up to 6000 PSI)

- Optional Spade Hook With Optional Hydraulic Thumb
- Optional Mounts Pin-On, Pin Grabber or Blank Plate
- 17 in (43.2 cm) Diameter Rotor
- 2 3/16 in (55.56 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1800-2500 RPM
- Steel Deflector Chains
- 37 mm Synchronous Belt
- Optional Tilt Hitch Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)

(800)828-7624 / (320)848-6266

LOFTNESS.COM



## 2025 RETAIL PRICING

# BATTLE AX® - 30 SERIES

SPECS	Width of Cut in Inches	41	51							
	Recommended Excavator Weight Range (in Pounds)	18K-36K	18K-36K							
	Overall Width in Inches	56.375	66.375							
	Number of Teeth	20	26							
	Weight Without Mount in Pounds	2,010	2,210							
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	45-150	45-150							
	Hydraulic Flow Range (GPM)	20-60	20-60							
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column.	41	51							
	Size									
1	41 Inches	\$33,603								
	51 Inches	51BX30		\$35,203						
2	Teeth									
	Reversible Planer Teeth p/n N49366 (\$41.00 ea.)	Q	\$820	\$1,070						
	Reversible Planer Hard p/n 203014 (\$61.00 ea.)	Н	\$1,220	\$1,590						
	Double Carbide Teeth p/n N49090 (\$75.00 ea.)	S	\$1,500	\$1,950						
3	Hydraulic Motor									
	Piston Motor - 105cc 20-60 GPM up to 6000 PSI - Case Drain Required	57	Included	Included						
4	Belt Drive Combination									
	20-60 GPM	Α	Included	Included						
OPTIONS	Spade Hook	Н	\$190	\$190						
	Thumb Attachment (Requires Spade Hook)	Т	\$1,030	\$1,030						
	Mount		I.							
5	Blank Plate Mount	N49170	\$290	\$290						
	Common Factory/OEM Specific Mount		\$1,600	\$1,600						
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)	\$2,200	\$2,200							
	Custom Mount, Pin Grabber Style (Welded Pins)		\$1,400	\$1,400						
	Tilt Hitch		\$3,750	\$3,750						
	Special Aftermarket Mount (Call for Pricing and Availability)		CALL	CALL						

PRODUCT CODE		<b>)</b>		<b>)</b> }		<b>)</b> }		<b>)</b> }		<b>&gt;&gt;</b>	
GROUP	1		2		3		4		OPTIONS		5



NOTE: Hoses and couplers from Power Unit to Head Are NOT Included. Case Drain Required.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

