12-TON FERTILIZER SPREADER





FEATURES

12-Ton Fertilizer Spreaders

- Variable Rate Ready

- Hydraulic Conveyor Drive
- Dual Stainless-Steel Conveyor Chains
- Dual Stainless-Steel Spinners
- 40- to 90-Foot-Wide Spread Pattern
- 41-Inch Frame Clearance
- 80- to 120-Inch Adjustable Wheel Spacing
- Optional 90- to 152-Inch Adjustable Wheel Spacing
- Obstruction-Free Interior
- 409 Stainless-Steel Hopper

- 50-Degree Hopper Slope
- Single Bearing Design
- Adjustable Hitch
- Optional Two-Section Spreading
- Optional Controlled Spinner Drive
- Optional Integral Scale
- Optional Steerable Hitch
- Optional Dual Wheels
- Optional Roll Tarp
- Multiple Tire Options

(800)828-7624 / (320)848-6266

LOFTNESS.COM



2025 RETAIL PRICING

12-TON FERTILIZER SPREADERS

| GROUP | Circle/select 1 item from each group in the proper size/model column and product code column. | PRODUCT | F1210 |
|---|---|---------|-----------|
| | 12-Ton Fertilizer Spreaders | F1210 | \$57,523 |
| | Spread Width | | |
| | 40' Driving Interval | 4 | \$0 |
| | 50' Driving Interval | 5 | \$0 |
| 1 | 60' Driving Interval | 6 | Included |
| | 80' Driving Interval | 8 | \$0 |
| | 88' Driving Interval | Α | \$0 |
| | 90' Driving Interval | 9 | \$0 |
| | Tire Size | | |
| 2 | 320/90R50 (12.4R50) Lugged Tire - 10 on 13.189 BC | 4 | \$4,000 |
| | 380/90R46 (14.9R46) Lugged Tire - 10 on 13.189 BC | 2 | Included |
| | 480/80R42 (18.4R42) Lugged Tire - 10 on 13.189 BC - Singles Only | R | \$3,000 |
| | 710/70R38 Lugged Tire - 10 on 13.189 BC - Singles Only | F | \$9,500 |
| | No Tires - 10 on 13.189 BC - Singles Only | Н | (\$3,000) |
| 3 | Apron Drive Variable Rate Ready (VRR) | | |
| | Hydraulic Drive Raven 22 Pin - Requires HSD, Not Available on CSD - Includes Spinner RPM Sensor | W | \$320 |
| | Hydraulic Drive Raven 37 Pin - Includes Spinner RPM Sensor | Х | Included |
| | Hydraulic Drive Raven 37 Pin - (Two Section) - Includes Spinner RPM Sensor | Υ | \$4,900 |
| | Hydraulic Drive Raven 47 Pin - Includes Spinner RPM Sensor (JD Rate Controller 2000 Ready) | Z | \$600 |
| | Hydraulic Drive Raven 47 Pin - (Two Section) - Includes Spinner RPM Sensor | Α | \$5,400 |
| | Hydraulic Drive ISO Ready - Includes Spinner RPM Sensor | Т | \$0 |
| | Hydraulic Drive ISO Ready - (Two Section) - Includes Spinner RPM Sensor | U | \$4,900 |
| | Spinner Drive | | |
| 4 | Hydraulic Spinner Drive (HSD) - Fixed Speed | Н | (\$320) |
| | Controlled Spinner Drive (CSD) - Compensated Speed | С | Included |
| 5 | Wheel Struts, Steering & Scale Options (No Brakes) | | |
| | 74"-144" Tread on Center - Non-Steerable - Dual Ready | 8 | Included |
| | 74"-144" Tread on Center - Non-Steerable, w/ Scale (Monitor is Optional) - Dual Ready | 9 | \$4,000 |
| | 74"-144" Tread on Center - Steerable, w/ Scale (Monitor is Optional) - Dual Ready | D | \$5,000 |
| OPTIONS PLEASE CALL FACTORY TO VERIFY AVAILABILITY | Duals - 380/90R46 (14.9R46) Lugged Tire - 20" Spacing (Requires #2 Group 2) | 3 | \$16,940 |
| | Duals - 380/90R46 (14.9R46) Lugged Tire - 22" Spacing (Requires #2 Group 2) | 2 | \$16,940 |
| | Duals - 320/90R50 (12.4R50) Lugged Tire - 20" Spacing (Requires #4 Group 2) | 5 | \$20,940 |
| | Duals - 320/90R50 (12.4R50) Lugged Tire - 22" Spacing (Requires #4 Group 2) | 4 | \$20,940 |
| | Tarp (Installation not Included) | Т | \$4,990 |
| | John Deere GS2 Ready (Requires Apron Drive Code "T") | J | \$600 |
| | Raven ISO CAN Node (Requires ISO Ready) | ı | \$5,620 |
| | Raven SCS660 Controller (Req.22 Pin) (Includes Harness to Spreader) | R | \$5,950 |
| | GPS Speed Sensor | G | \$600 |
| | Scale Monitor - Digistar GT 400 (Requires Scale) | М | \$1,780 |
| | Ladder | L | \$1,400 |





(800)828-7624 / (320)848-6266

LOFTNESS.COM

