TIMBER AX SKID STEER MULCHING HEAD







FEATURES

Timber Ax Forestry Mulching Heads for Skid Steers

- High Pressure Gear-Type Motor
- 22-40 GPM up to 4300 PSI 85 Hyd. HP Max
- Upward Rotation of Knives
- Adjustable Shear Bar
- Special Alloy, Sharpened Blades
- Rigid, Pocket-Style Knife Mounts
- Dual Cross-Over Relief Protection
- Heavy-Duty, Bearing Block
- 2 3/16 Inch Rotor Bearings
- Bearing Anti-Wrap Protection

- 1700 RPM 17 Inch Diameter Rotor
- 4-Groove Banded Belt
- Spring-Loaded Belt Tensioner
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Skid Shoes Adjustable 1 to 3 Inches
- Pressure Gauge to Monitor Capacity
- Steel Deflector Chains
- Fast Rotor Shutdown
- Hoses & Hose Holder Are Included

BUILD & PRICE

TIMBER AX

	Width of Cut in Inches	73	83
	Overall Width in Inches	91.5	101.5
SPECS	Number of Knives	16	18
SPE	Weight in Pounds	2,416	2,632
	Hydraulic Horsepower Range (Hydraulic Horsepower = GPM x PSI / 1714)	40-85	40-85
	Max Hydraulic Pressure in PSI	4,300	4,300

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column.	PRODUCT CODE	73	83
1	Size			
•	73 Inches	73TA	\$31,594	
	83 Inches	83TA		\$32,514
	Auxilary Hydraulic Flow (GPM)			
	22-25.9 GPM	MP	\$0	\$0
2	26-30.9 GPM	MQ	\$0	\$0
	31-36.9 GPM	MR	\$0	\$0
	37-40.9 GPM	MS	\$0	\$0

PRODUCT	>>	\$
GROUP 1	2	TOTAL LIST PRICE

NOTE: Generic hoses are included. Couplers are NOT included.

*Hoses: 3/4" x 108" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Patent #6,871,485

Related Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With **Products** Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

