

# BAD AX - DISC MULCHER

## SKID STEER MULCHING HEAD





## FEATURES

### Forestry Mulching Heads for *Skid Steers*

- Instant Torque Radial Piston High-Pressure Motor
- 36-50 GPM up to 5000 PSI
- 70-120 Hydraulic Horsepower Required
- 60 Inch Diameter Disc - 1.25" Max Thickness
- No Welding on Disc - **Fully Machined**
- 200 MPH Tip Speed @ Up to 1100 RPM
- Quadco Reversible Teeth
- **Bolt-on Replaceable Tooth Mounts**
- Bearing Anti-Wrap Protection
- Premium Strength Steel Body & Disc
- Controlled Discharge Deflector
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Re-Cutter Bar
- Pressure Gauge to Monitor Capacity
- Anti-Cavitation Shut Down Circuit
- Universal Skid-Steer Mount
- Hoses Are Included (Couplers Are Not)

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD  
& PRICE



SPECS	Width of Cut in Inches	60
	Overall Width in Inches	67
	Number of Teeth	44
	Weight Without Mount in Pounds	2,643
	Hydraulic Horsepower Required (Hydraulic HP = GPM X PSI/1714)	70-120
	Radial Piston Motor Max Hydraulic Pressure in PSI	5,000

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	60
<b>Teeth</b>			
1	Quadco 4 Point Beaver Teeth - N156042 (\$21.00 ea.)	60BA	\$30,586
<b>Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)</b>			
2	36-50 GPM - Piston Motor - 5000 PSI - 70-120 Hydraulic HP	4	\$8,130

PRODUCT CODE	60BA	4	<b>\$37,486</b>
GROUP	1	2	

NOTE: Hoses Are Included. **Couplers Are NOT Included.**  
 \*Main Hoses: 1" with #16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

**Related Products** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 120,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

