

BATTLE AX® - 10 SERIES

EXCAVATOR MULCHING HEAD



BATTLE AX

FEATURES

Forestry Mulching Heads for **7,000-10,000 lb Excavators**

- **“Battle Ax” Rotor Design** - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- 45cc Fixed Displacement Gear Motor
- 2 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 20-70 Hydraulic HP (15-19.9 GPM @ up to 4100 PSI)
- Optional Spade Hook
- Optional Mounts - Pin-On, Pin Grabber or Blank Plate
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1750-2300 RPM
- Steel Deflector Chains
- Case Drain Highly Recommended

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**



650 Main Street South | Hector, MN 55342

SPECS	Width of Cut in Inches	25
	Recommended Excavator Weight Range (in Pounds)	7K-10K
	Overall Width in Inches	45
	Number of Teeth	16
	Weight Without Mount (in Pounds)	620
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	20-70
	Hydraulic Flow Range (GPM)	15-19.9

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column. →	PRODUCT CODE	25
1	Size			
	25 Inches		25BX10	\$17,876
2	Teeth			
	Quadco 4 Point Beaver Teeth - N156042 (\$21.00 ea.)		Q	\$340
	Quadco Reversible Planer Teeth - 202970 (\$27.00 ea.)		P	\$440
	Double Carbide Teeth - 209036 (\$65.00 ea.)		S	\$1040
3	Hydraulic Motor			
	Gear Motor - 45cc 15-19.9 GPM up to 4100 PSI (Use with or without Case Drain*)		65	Included
4	Belt Drive Combination			
	15-19.9 GPM		A	Included
OPTIONS	OPTIONS			
	Spade Hook		H	\$190
5	Mount			
	Blank Plate Mount			\$100
	Common Factory/OEM Specific Mount			\$950
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)			\$950
	Custom Mount, Pin Grabber Style (Welded Pins)			\$750
	Special Aftermarket Mount (Call for Pricing and Availability)			CALL

PRODUCT CODE

	»		»		»		»		»	
GROUP	1	2	3	4	OPTIONS	5				

\$
TOTAL LIST PRICE

NOTE: **Hoses and Couplers from Power Unit to Head Are NOT Included.**

*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

