

# BATTLE AX® - 30 SERIES

## EXCAVATOR MULCHING HEAD



# BATTLE AX

## FEATURES

### Forestry Mulching Heads for **18,000-36,000 lb Excavators**

- “Battle Ax” Rotor Design - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - Reversible Planer, Hard Surface Planer or Double Carbide
- 105cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 45-150 Hydraulic HP (20-60 GPM @ up to 6000 PSI)
- Optional Spade Hook - With Optional Hydraulic Thumb
- Optional Mounts - Pin-On, Pin Grabber or Blank Plate
- 17 in (43.2 cm) Diameter Rotor
- 2 3/16 in (55.56 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1800-2500 RPM
- Steel Deflector Chains
- 37 mm Synchronous Belt
- **Optional Tilt Hitch** - Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

**BUILD  
& PRICE**



SPECS	Width of Cut in Inches		<b>41</b>	<b>51</b>	
	Recommended Excavator Weight Range (in Pounds)		18K-36K	18K-36K	
	Overall Width in Inches		56.375	66.375	
	Number of Teeth		20	26	
	Weight Without Mount in Pounds		2,010	2,210	
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)		45-150	45-150	
	Hydraulic Flow Range (GPM)		20-60	20-60	
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	<b>41</b>	<b>51</b>
<b>Size</b>					
1	41 Inches		<b>41BX30</b>	\$33,606	
	51 Inches		<b>51BX30</b>		\$35,206
<b>Teeth</b>					
2	Reversible Planer Teeth p/n N49366 (\$41.00 ea.)		<b>Q</b>	\$820	\$1,070
	Reversible Planer Hard p/n 203014 (\$61.00 ea.)		<b>H</b>	\$1,220	\$1,590
	Double Carbide Teeth p/n N49090 (\$227.00 ea.)		<b>S</b>	\$4,540	\$5,900
<b>Hydraulic Motor</b>					
3	Piston Motor - 105cc 20-60 GPM up to 6000 PSI - Case Drain Required		<b>57</b>	Included	Included
<b>Belt Drive Combination</b>					
4	20-60 GPM		<b>A</b>	Included	Included
<b>OPTIONS</b>					
	Spade Hook		<b>H</b>	\$190	\$190
	Thumb Attachment (Requires Spade Hook)		<b>T</b>	\$1,030	\$1,030
<b>Mount</b>					
5	Blank Plate Mount		<b>N49170</b>	\$290	\$290
	Common Factory/OEM Specific Mount			\$1,600	\$1,600
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)			\$2,200	\$2,200
	Custom Mount, Pin Grabber Style (Welded Pins)			\$1,400	\$1,400
	Tilt Hitch			\$3,750	\$3,750
	Special Aftermarket Mount (Call for Pricing and Availability)			CALL	CALL

PRODUCT CODE		»		»		»		»		»	
	GROUP	1	2	3	4	OPTIONS	5				

\$
TOTAL LIST PRICE

NOTE: Hoses and couplers from Power Unit to Head Are NOT Included. Case Drain Required.

(800)828-7624 / (320)848-6266

LOFTNESS.COM



USD - FOB Factory - Uncrated - Prices Effective 3/4/26 (Subject to Change)  
650 Main Street South | Hector, MN 55342