

BATTLE AX® - 30 SERIES

EXCAVATOR MULCHING HEAD

LOFTNESS 


FEATURES

Forestry Mulching Heads for **18,000-36,000 lb Excavators**

- “Battle Ax” Rotor Design - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - Quadco Reversible Planer Teeth, Hard-Surfaced Quadco Reversible Planer Teeth or Double Carbide Teeth
- 105cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 45-150 Hydraulic HP
- (20-60 GPM @ up to 6000 PSI)
- Optional Spade Hook - With Optional Hydraulic Thumb
- Optional Mounts - Pin-On, Pin Grabber or Blank Plate
- 17 in (43.2 cm) Diameter Rotor
- 2 3/16 in (55.56 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1800-2500 RPM
- Steel Deflector Chains
- 37 mm Synchronous Belt
- **Optional Tilt Hitch** - Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)

(800)828-7624 / (320)848-6266
LOFTNESS.COM
**BUILD
& PRICE**


650 Main Street South | Hector, MN 55342

SPECS	Width of Cut in Inches		41	51	
	Recommended Excavator Weight Range (in Pounds)		18K-36K	18K-36K	
	Overall Width in Inches		56.375	66.375	
	Number of Teeth		20	26	
	Weight Without Mount in Pounds		2,010	2,210	
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)		45-150	45-150	
	Hydraulic Flow Range (GPM)		20-60	20-60	
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	41	51
1	Size				
	41 Inches	41BX30	\$35,376		
	51 Inches	51BX30		\$37,056	
2	Teeth				
	Quadco Reversible Planer Teeth p/n N49366 (\$50 ea.)	Q	\$1,000	\$1,300	
	Hard-Surfaced Quadco Reversible Planer Teeth p/n 203014 (\$76 ea.)	H	\$1,520	\$1,980	
	Double Carbide Teeth p/n N49090 (\$170.00 ea.)	S	\$3,400	\$4,420	
3	Hydraulic Motor				
	Piston Motor - 105cc 20-60 GPM up to 6000 PSI - Case Drain Required	57	Included	Included	
4	Belt Drive Combination				
	20-60 GPM	A	Included	Included	
OPTIONS	Options - Not Compatible with Factory Thumb				
	Spade Hook	H	\$190	\$190	
	Thumb Attachment (Requires Spade Hook)	T	\$1,030	\$1,030	
5	Mount - Not Compatible with Factory Thumb				
	Blank Plate Mount	N49170	\$290	\$290	
	Common Factory/OEM Specific Mount		\$1,600	\$1,600	
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)		\$2,200	\$2,200	
	Custom Mount, Pin Grabber Style (Welded Pins)		\$1,400	\$1,400	
	Tilt Hitch		\$3,750	\$3,750	
	Special Aftermarket Mount (Call for Pricing and Availability)		CALL	CALL	

PRODUCT CODE		»		»		»		»		»	
GROUP	1		2		3		4		OPTIONS		5

\$
TOTAL LIST PRICE

NOTE: Hoses and couplers from Power Unit to Head Are NOT Included. Case Drain Required.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD
& PRICE

