

BATTLE AX - H SERIES

PRIME MOVER MULCHING HEAD




BATTLE AX

FEATURES

Forestry Mulching Heads for *Prime Movers With 95-150 Horsepower*

- "Battle Ax" Rotor Design - Uses Built-In Depth Gauges to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- Two-Stage Cutting Chamber - Uses 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs - Reversible Planer Knives, Hard-Surfaced Planer or Double Carbide
- Variable Displacement Piston-Type Motor 90-110 CC
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar
- Replaceable Secondary Shear Bar
- Manual or Hydraulic Pusher Bar
- Welded Claw Hooks on Pusher Bar
- 17 Inch Diameter Rotor
- 1" Wall Rotor Tube
- 2-1/2" Piloted Double Taper Roller Bearings
- Machined Bearing Anti-Wrap
- Rotor Speed 1600-2300 RPM
- Synchronous Belt Drive
- On Board PSI Gauge to Monitor Capacity
- Replaceable Skid Shoes
- Optional Universal Skid Steer Mount
- Optional Custom Mounts Available
- Optional Bolt-In Liner

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD
& PRICE



SPECS	Cutting Width in Inches	71	84
	Overall Width in Inches	88.25	101.25
	Number of Teeth	36	42
	Weight in Pounds	3,440	3,792
	Required Hydraulic HP	95-150HP	95-150HP

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column. →			PRODUCT CODE	71	84
Size							
1	71 Inches	71BH	\$38,296				
	84 Inches	84BH				\$39,806	
Teeth							
2	Quadco Reversible Knives - N49366 (\$41.00 each)	Q	\$1,480			\$1,720	
	Hard-Surfaced Quadco Reversible Knives - 203014 (\$61.00 each)	H	\$2,200			\$2,560	
	Standard Double Carbide - N49090 (\$227.00 each)	S	\$8,170			\$9,530	
Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714)							
3	Variable Displacement Piston Motor (Closed Loop)	41	\$12,620			\$12,620	
	Variable Displacement Piston Motor (Open Loop)	48	\$12,110			\$12,110	
Auxiliary Hydraulic Flow (GPM)							
4	33-37.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	A	\$0			\$0	
	38-42.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	B	\$0			\$0	
	43-47.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	D	\$0			\$0	
	48-52.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	H	\$0			\$0	
	53-57.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	I	\$0			\$0	
	58-62.9 (Variable Disp. Motor) - up to 6000PSI Standard Speed	J	\$0			\$0	
	33-37.9 (Variable Disp. Motor) - up to 6000PSI High Speed	T	\$0			\$0	
	38-42.9 (Variable Disp. Motor) - up to 6000PSI High Speed	U	\$0			\$0	
	43-47.9 (Variable Disp. Motor) - up to 6000PSI High Speed	V	\$0			\$0	
	48-52.9 (Variable Disp. Motor) - up to 6000PSI High Speed	D	\$0			\$0	
	53-57.9 (Variable Disp. Motor) - up to 6000PSI High Speed	H	\$0			\$0	
	58-62.9 (Variable Disp. Motor) - up to 6000PSI High Speed	I	\$0			\$0	
Auxiliary Hydraulic Pressure (PSI)							
5	2800-3499 PSI	1	\$0			\$0	
	3500-3899 PSI	2	\$0			\$0	
	3900-4399 PSI	3	\$0			\$0	
	4400-5099 PSI	4	\$0			\$0	
	5100-5999 PSI	5	\$0			\$0	
OPTIONS							
OPTIONS	Universal Skid Steer Mount	S	\$1,130			\$1,130	
	Pusher, Hydraulic	H	\$2,350			\$2,350	
	Bolt-in Liner (71BH - 209043) (81BH - 209044)	L	\$920			\$1,000	

PRODUCT CODE

1

»

2

»

3

»

4

»

5

»

OPTIONS

\$

TOTAL LIST PRICE

NOTE: Hoses and couplers are NOT included.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

