

BATTLE AX® - S SERIES

SKID STEER MULCHING HEAD



FEATURES

*Forestry Mulching Heads for **Skid Steers***

- “Battle Ax” Rotor Design - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Less Passes
- **Three Tooth Designs** - Quadco Reversible Planer Teeth, Hard-Surfaced Quadco Reversible Planer Teeth or Double Carbide Teeth
- Variable Disp. Piston-Type Motor 90-110cc
- Variable Disp. Piston-Type Motor 90-110cc with Brake
- Fixed Disp. High Pressure Gear-Type Motor
- **GPM Rating** 28-62.9 GPM
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Adjustable Tree-Pusher Bar
- Welded Claw Hooks on Pusher Bar
- 17 Inch Diameter Rotor
- 2-3/16" Piloted Double Taper Roller Bearings
- Machined Bearing Anti-Wrap
- Rotor Speed 1600-2300 RPM
- Synchronous Belt Drive
- On-Board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Replaceable Skid Shoes
- Hoses Are Included (No Couplers)
- Improved Hose Routing
- Universal Skid Steer Mount
- Optional Bolt-in Liner
- Optional Hydraulic Braking

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**



650 Main Street South | Hector, MN 55342

2026 RETAIL PRICING

BATTLE AX® - S SERIES

SPECS	Width of Cut in Inches		61	71	
	Overall Width in Inches		79.1	89.1	
	Number of Teeth		30	36	
	Weight in Pounds		2,604	2,841	
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. —>		PRODUCT CODE	61	71
1	Size				
	61 Inches	61BS	\$30,126		
	71 Inches	71BS			\$31,836
2	Teeth				
	Quadco Reversible Planer Teeth - N49366 (\$50 ea.)	Q	\$1,500	\$1,800	
	Hard-Surfaced Quadco Reversible Planer Teeth - 203014 (\$76 ea.)	H	\$2,280	\$2,740	
	Double Carbide Teeth - N49090 (\$170.00 ea.)	S	\$5,100	\$6,120	
3	Hydraulic Motor System (Hydraulic Horsepower = GPM x PSI / 1714) VERIFY TO CHOOSE CORRECT MODEL				
	Fixed Disp. High Pressure Gear Motor - 50-85 Hydraulic Horsepower**	66	\$5,110	\$5,110	
	Variable Displacement Piston Motor - (Open Loop) 50-150 Hydraulic Horsepower*	44	\$12,110	\$12,110	
	Variable Displacement Piston Motor - (Closed Loop) 50-150 Hydraulic Horsepower*	45	\$12,620	\$12,620	
	Variable Displacement Piston Motor - (Open Loop) (Hydraulic Brake) 50-150 Hydraulic Horsepower*	67	\$13,610	\$13,610	
4	Auxiliary Hydraulic Flow (GPM)				
	28-32.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	T	\$0	\$0	
	33-37.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	A	\$0	\$0	
	38-42.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	B	\$0	\$0	
	43-47.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	D	\$0	\$0	
	48-52.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	H	\$0	\$0	
	53-57.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	I	\$0	\$0	
	58-62.9 GPM (Variable Disp. Motor) - up to 6000 PSI - Standard Speed	J	\$0	\$0	
	32-37.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	T	\$0	\$0	
	38-41.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	U	\$0	\$0	
	42-47.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	V	\$0	\$0	
	48-52.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	D	\$0	\$0	
	53-57.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	H	\$0	\$0	
	58-62.9 GPM (Variable Disp. Motor) - up to 6000 PSI - High Speed Option	I	\$0	\$0	
	28-30.9 GPM (Fixed Disp. Motor) - up to 4300 PSI	E	\$0	\$0	
	31-35.9 GPM (Fixed Disp. Motor) - up to 4300 PSI	F	\$0	\$0	
	36-40.9 GPM (Fixed Disp. Motor) - up to 4300 PSI	G	\$0	\$0	
	5	Auxiliary Hydraulic Pressure (PSI)			
Fixed Displacement High Pressure Gear Motor		0	\$0	\$0	
2800-3499 PSI - (Variable Displacement Motor System)		1	\$0	\$0	
3500-3899 PSI - (Variable Displacement Motor System)		2	\$0	\$0	
3900-4399 PSI - (Variable Displacement Motor System)		3	\$0	\$0	
4400-5099 PSI - (Variable Displacement Motor System)		4	\$0	\$0	
5100-5999 PSI - (Variable Displacement Motor System)		5	\$0	\$0	
OPTIONS	Right Hand Hose Conversion Kit, 6000 PSI (209064) (Variable Disp. Motor)	V	\$750	\$750	
	Right Hand Hose Conversion Kit, 4000 PSI (209065) (Fixed Disp. Motor)	F	\$490	\$490	
	Bolt-in Liner (61BS - 209043) (71BS - 209044)	L	\$860	\$910	

PRODUCT CODE

GROUP

1

2

3

4

5

OPTIONS

\$

TOTAL LIST PRICE

NOTE: Hoses are included. **Couplers are NOT included.**

*Variable Motor: 1" with -16 MORB Male O-ring and #12 adapter, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

**Fixed Motor: 3/4" with -12 MORB Male O-ring, Case Drain Line (required) : 1/2" - #8 MORB Male O-ring

(800)828-7624 / (320)848-6266

LOFTNESS.COM

BUILD
& PRICE

USD - FOB Factory - Uncrated - Prices Effective 3/4/26 (Subject to Change)

650 Main Street South I Hector, MN 55342

L10084 - 8/10/26