

FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC



FLAIL MOWER

FEATURES

*Flail Mowers for **Skid Steers***

- High Pressure Gear-Type Motor (With or Without Case Drain)
- 15-43 GPM up to 4200 PSI (With Case Drain)
- 15-32 GPM up to 3500 PSI (Without Case Drain)
- Two Knife Designs - Flail or Duckfoot
- Toolless Knife Change
- **Heavy-Duty Bearing Block**
- 3-Groove Banded Belt
- **1-7" Cutting Height**
- 1/4" End Plates
- 5 1/2" OD x 3/8" Wall Roller Tube
- 1 1/2" Bearing on Gauge Roller
- Added Gauge Roller Bearing Protection
- 1500-2050 RPM Rotor Speed
- Premium Strength Steel Housing
- Full-Width Gauge Roller with Roller Scraper
- 1 3/4" Rotor Bearings
- Anti-Wrap Bearing Protection
- Hoses Are Included (Couplers Are Not)
- **Optional Floating Hitch with Gauge Wheels**

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**



650 Main Street South | Hector, MN 55342

SPECS	Width of Cut in Inches	72	90
	Overall Width in Inches	83	101
	Number of Knives (Flail / Duckfoot)	96 / 48	120 / 60
	Weight Without Floating Hitch (in Pounds)	1,360	1,570
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor Without Case Drain	3,500	3,500
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor With Case Drain	4,200	4,200
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. →			PRODUCT CODE	72	90
Size						
1	72 Inches	72HM	\$11,406			
	90 Inches	90HM			\$12,296	
Knife						
2	Duckfoot	D	\$0	\$0		
	Flail	F	\$0	\$0		
Hydraulic System						
3	Gear Motor - No Case Drain* (15-32.9 GPM) (3500 PSI max)	61	\$4,020	\$4,020		
	Gear Motor - With Case Drain** (15-43.9 GPM) (4200 PSI max)	62	\$3,130	\$3,130		
Auxiliary Hydraulic Flow (GPM)						
4	15-20.9 GPM	A	\$0	N/A		
	21-27.9 GPM	B	\$0	\$0		
	28-32.9 GPM	C	\$0	\$0		
	33-36.9 GPM (Requires Hydraulic System Code "62")	D	\$0	\$0		
	37-43.9 GPM (Requires Hydraulic System Code "62")	E	\$0	\$0		
OPTIONS	Floating Hitch with Gauge Wheels	F	\$3780	\$3780		

PRODUCT CODE		»		»		»		»	
GROUP	1		2		3		4		OPTIONS

\$
TOTAL LIST PRICE

NOTE: Hoses are included. Couplers are NOT included.
 *Hoses: 3/4" #12 MORB - Male O-ring, NO Case Drain Line Required
 **Hoses: 3/4" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" - #8MORB

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

