

TIMBER AX

SKID STEER MULCHING HEAD



FEATURES

Timber Ax Forestry Mulching Heads for Skid Steers

- High Pressure Gear-Type Motor
- 22-40 GPM up to 4300 PSI - 85 Hyd. HP Max
- **Upward Rotation of Knives**
- **Adjustable Shear Bar**
- **Special Alloy, Sharpened Blades**
- Rigid, Pocket-Style Knife Mounts
- Dual Cross-Over Relief Protection
- Heavy-Duty, Bearing Block
- 2 3/16 Inch Rotor Bearings
- Bearing Anti-Wrap Protection
- 1700 RPM - 17 Inch Diameter Rotor
- 4-Groove Banded Belt
- Spring-Loaded Belt Tensioner
- Adjustable Tree-Pusher Bar
- Claw Hooks on Pusher Bar
- Skid Shoes - Adjustable 1 to 3 Inches
- Pressure Gauge to Monitor Capacity
- Steel Deflector Chains
- Fast Rotor Shutdown
- Hoses & Hose Holder Are Included

(800)828-7624 / (320)848-6266

LOFTNESS.COM

**BUILD
& PRICE**



SPECS	Width of Cut in Inches	73	83
	Overall Width in Inches	91.5	101.5
	Number of Knives	16	18
	Weight in Pounds	2,416	2,632
	Hydraulic Horsepower Range (Hydraulic Horsepower = GPM x PSI / 1714)	40-85	40-85
	Max Hydraulic Pressure in PSI	4,300	4,300

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column. →		PRODUCT CODE	73	83
1	Size					
	73 Inches		73TA	SPECIAL ORDER ONLY		
	83 Inches		83TA			\$32,516
2	Auxiliary Hydraulic Flow (GPM)					
	22-25.9 GPM		MP	\$0	\$0	
	26-30.9 GPM		MQ	\$0	\$0	
	31-36.9 GPM		MR	\$0	\$0	
	37-40.9 GPM		MS	\$0	\$0	

PRODUCT CODE		»		\$
GROUP	1		2	

NOTE: Generic hoses are included. **Couplers are NOT included.**

*Hoses: 3/4" x 108" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Patent #6,871,485

Related Products Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266

LOFTNESS.COM

