

» FLAIL MOWER

LOFTNESS 

FLAIL MOWER

SKID STEER & PTO



Proudly American.

SKID STEER

FLAIL MOWER



PLENTY OF POWER

A reliable high-pressure gear motor allows the flail mower to slice through some of the toughest grasses, weeds and brush. Multiple options are available to accommodate low- and high-flow skid steers with or without a case drain.

3/4" CUTTING CAPACITY

GO WITH THE FLOAT

Optional Floating Hitch

An optional floating hitch helps prevent the flail mower from gouging the ground. It includes adjustable caster wheels that follow the ground contour to produce an even cut. The floating hitch also makes operation easier by eliminating the need for constant height adjustments.




PTO

FLAIL MOWER

DESIGNED FOR DURABILITY

The flail mower was engineered with large-diameter bearings, a reliable drive system and premium strength steel housing. It's built to last for years of use in tough conditions, making it a perfect fit for many applications, from large properties to right-of-ways.



CHOOSE YOUR WEAPON

The flail mower can be equipped with duckfoot knives to produce a finer cut in easier cutting conditions or flail knives for use in more challenging vegetation. Easily change between knives without having to use any tools.



Every rotor is **perfectly balanced** at high speeds using the latest computer technology.

An adjustable full-width gauge roller provides a **consistent cutting height**.

The PTO-driven flail mower from Loftness adds versatility to your existing tractor with 540 RPM PTO and 25-70 horsepower. This model can attach via Cat. I or II, free-link or quick hitch.

- » **Fine-cut, reversible knives** slice through material up to 3/4" in diameter.
- » The flail mower can be **mounted in the center of the tractor or 14 inches offset to the right**.
- » A **heavy-duty gearbox** is rated for 70 horsepower.



Explore All Features

SKID STEER SPECIFICATIONS

Model	72HM	90HM
Flow Requirement	15-43.9 GPM @ 4200 PSI (with case drain) or 15-32.9 GPM @ 3500 PSI (without case drain)	21-43.9 GPM @ 4200 PSI (with case drain) or 21-32.9 GPM @ 3500 PSI (without case drain)
Max Hydraulic HP Input	90	90
Cutting Width	72" (1.83 m)	90" (2.29 m)
Overall Width	83" (2.11 m)	101" (2.57 m)
Number of Knives (Flail/Duckfoot)	96/48	120/60
Rotor Speed	1500-2050 RPM	1500-2050 RPM


PTO SPECIFICATIONS

Model	72M	90M
PTO Horsepower Range	25-70	30-70
Cutting Width	72" (1.83 m)	90" (2.29 m)
Overall Width	84" (2.13 m)	102" (2.59 m)
Number of Knives	96 (48 sets)	120 (60 sets)
Weight	1,040 LBS (471.7 kg)	1,200 LBS (544.3 kg)

DURABILITY RUNS DEEP WITH OUR FULL LINE OF EQUIPMENT



**MULCHING HEADS » BRUSH CUTTERS » DISC MULCHERS » FLAIL MOWERS
STUMP GRINDERS » HYDRAULIC COOLERS » MECHANICAL TRIMMERS**



BUILD & PRICE TOOL

Like what you see? Start customizing your own flail mower with our online tool.



FIND A DEALER



Prefer to talk to a local expert? Find your nearest Loftness dealer and get straight answers.

Proudly American. Employee Owned.

At Loftness, we're proud of the products we make at our local manufacturing facility in Hector, Minnesota. And we take things personally when it comes to providing customers with the most durable, highest performing equipment that's backed by the best customer support. That's because we're 100% employee-owned, so every single one of us has a stake in your success.



Loftness Specialized Equipment
650 Main Street South • Hector, Minnesota 55342 USA
US & Canada: 800-828-7624 | International 320-848-6266
info@loftness.com | www.loftness.com