» STONE CRUSHER


LOFTNESS

STONE AX™



Proudly American.

Explore all Features






CONTROLLED CRUSH

The Stone Ax™ has an adjustable front anvil to help control the final particle size. It also features a rear hydraulic door, allowing operators to further control how thoroughly stones are processed on the fly. The rear door is equipped with specialized fins that allow soil to pass through, so more power is focused on crushing stones.



ROCK-HARD DEPENDABILITY

Large rotor bearings. One-inch-thick steel drum walls. A Hardox® lined body. Everything about the Stone Ax is designed for durability. We've also tested it in some of the hardest material that exists, so you can count on it getting you through the most demanding jobs — day in and day out.



DESIGNED TO DOMINATE

SPECIALIZED ROTOR DESIGN

The tooth pattern is engineered to complete jobs faster, while providing optimum rotor balance. It's a true one-pass machine for many applications.

6" STONE CAPACITY


BUILT SOLID TO BUST STONE


Whether you're cleaning up farmland, preparing a construction site or improving a back road, nothing gets the job done like Loftness. Our stone crusher attachment is designed to work harder, last longer and perform better than anything else. Because if it didn't...our name wouldn't be on it.



275CC RADIAL PISTON MOTOR

When crushing stones, you don't want to come up short on power. That's why we gave the Stone Ax a large 275cc radial piston motor that leads the industry with exceptional torque and works through the toughest material without slowing down. It requires a skid steer with 34 to 50 GPM up to 5,000 PSI.





REALLY TOUGH TEETH

The carbide teeth on the Stone Ax are designed to withstand harsh working conditions. If any of them need to be replaced, it can be done easily on the jobsite.

SPECIFICATIONS

Model	*63SAH*
Overall Length	81" (2.1 m)
Overall Width	66" (1.7 m)
Working Width	63" (1.6 m)
Weight (without mount)	3,320 LBS (1,506 kg)
Max Working Depth	4" (10.2 cm)
Max Stone Size	6" (15.2 cm)
Rotor Diameter	20" (0.5 m)
Number of Teeth	46
Drum Wall Thickness	1" (2.5 cm)
Rotor Bearing Diameter	2.5" (6.4 cm)
Hydraulic Flow Range	34-50 GPM up to 5,000 PSI



» *The Stone Ax has a 6-inch stone capacity and a* ***4-inch working depth.***



» *An* ***integrated pressure gauge*** *helps operators keep the attachment working at the optimum hydraulic load for peak performance.*

» ***Bearings are protected*** *from the stone crushing operation to help maximize service life.*

» *A* ***63-inch working width*** *is the ideal size for covering the skid steer's tracks.*

DURABILITY RUNS DEEP WITH OUR FULL LINE OF EQUIPMENT



MULCHING HEADS » BRUSH CUTTERS » DISC MULCHERS » FLAIL MOWERS » STUMP GRINDERS

TREE SAWS » HYDRAULIC COOLERS » MECHANICAL TRIMMERS » STONE CRUSHERS



BUILD & PRICE TOOL

Like what you see? Start customizing your own Stone Ax™ with our online tool.

FIND A DEALER

Prefer to talk to a local expert? Find your nearest Loftness dealer and get straight answers.

Proudly American. Employee Owned.

At Loftness, we're proud of the products we make at our local manufacturing facility in Hector, Minnesota. And we take things personally when it comes to providing customers with the most durable, highest performing equipment that's backed by the best customer support. That's because we're 100% employee-owned, so every single one of us has a stake in your success.



LOFTNESS

Loftness Specialized Equipment
650 Main Street South • Hector, Minnesota 55342 USA
US & Canada: 800-828-7624 | International 320-848-6266
info@loftness.com | www.loftness.com

Specifications, data, and pricing information herein is subject to change without notice. Loftness is a registered trademarks of Loftness Corporation.

L10125 - Stone Ax - 11/26